



- 产品采用了系列化、模块化的设计思想，有广泛的适应性，本系列产品有极大的电机组合、安装位置和结构方案，传动比分级精细，转速型谱宽，满足不同的使用工况，实现机电一体化。
- R、K、F、S四大系列减速机采用单元结构模块化设计原理，大量减少了零部件种类和库存量，也大大缩短了交货周期。部件通用性强，维护成本低，特别是生产线，只需备用内部几个传动件即可保证整线正常生产的维修保养。
- 减速器效率高达96%，振动小、噪音低、性能优越、密封性能好、可在有腐蚀、潮湿等恶劣环境中连续工作。
- 带筋的高刚性铸铁箱体，齿轮采用高耐磨优质合金材料并经特种热处理及精密磨齿加工，确保轴平行度和定位的精度，这一切构成了齿轮传动的完美结合。

选型指南

- 减速机是按载荷平稳，每天工作时间一定和少量起停次数的情况设计的，而在实际使用中往往不是处于此种理想状况，因此必须按照实际情况的载荷类型、运行时间、起动频率来确定工作机系数 f_1 、原动机系数 f_2 、起动系数 f_3 。使其小于或等于选型表中的服务系数 f_B ，即 $f_1 \times f_2 \times f_3 \times f_4 \leq f_B$ 。或将工作机所需的转矩乘以服务系数($f_1 \times f_2 \times f_3$)应小于或等于减速机的许用转矩。

即 $T_N > T_2 \times f_1 \times f_2 \times f_3 \times f_4$

f_1 — 工作机系数 (见表1)

f_2 — 原动机系数 (见表2)

f_3 — 起动系数 (见表3)

f_4 — 环境温度工作系数(见表4)

T_2 — 工作机所需转矩

T_N — 减速机许用转矩(见第9页)

- K系列和T系列螺旋锥齿轮减速机如果只承受单向载荷则最好注明旋转方向(从输出端方向看)，这样有利于改善螺旋锥齿轮的受力状况。
- 我公司可承接特殊规格产品的订货，并可为客户提供专用设计服务。
- 随着技术进步，本公司产品设计和规格可能会有所更改，恕不另行通知。

- R series rigid tooth flank helical gear units, K series helical-bevel gear units, F series parallel shaft helical gear units, S series helical-worm gear units, T series spiral bevel gear units, have the advantages of small volume and big transmission torque.
- Designed and manufactured on the basis of modular combined system, the gear units have abundant combinations of motor, mounting positions and structure projects, the classifying class of transmission ratio is detailed, which meets the requirements of different working situation and realize mechatronics.
- R, K, F, S four main series gear units utilize the design principle of unit structure module, which reduces the categories and stocks of parts, and shortens the delivery period. High efficiency of drive, low consumption of power, and excellent performance.
- High rigidity cast iron housing with rib; the rigid tooth flank gear utilizes good-quality alloy steel, the surface is treated with carburizing quenching hardening treatment, refined processing of grounding, stable drive, low noise, big capacity of load, long using life.

Guidelines for the selection

- Gear units are designed under the circumstance of steady load, stated operating time per day and a few starting times, but the practical condition will be not as perfect as the designed circumstance. so we must confirm driven machine factor f_1 , prime mover factor f_2 , starting factor f_3 according to actual load type, operating time, starting frequency, let it less than or equal to the service factor f_B of selection table, viz $f_1 \times f_2 \times f_3 \times f_4 \leq f_B$. the needed torque of service machine multiply the service factor ($f_1 \times f_2 \times f_3$) should less than or equal to gear units' permissible torque.

Viz $T_N > T_2 \times f_1 \times f_2 \times f_3 \times f_4$

f_1 — driven machine factor (see table 1)

f_2 — prime mover factor (see table 2)

f_3 — starting factor (see table 3)

f_4 — ambient temperature work factor (see table 4)

T_2 — the needed torque of driven machine

T_N — gear units' permissible torque (see page 9)

- If the K series and T series spiral bevel gear units can only bear single direction load, please indicate the rotating direction (see from output side), which is good for improving the pressing state of the spiral bevel gear.
- We accept the orders of products of special specification, and provide our customer with exclusive design service.
- Design and specifications are subject to change without notice, Please forgive

载荷类型表

表 1

工作机系数

f1

工 作 机		日工作小时数			工 作 机		日工作小时数		
		≤0.5h	0.5~10h	>10h			≤0.5h	0.5~10h	>10h
污 水 处 理	浓缩器(中心传动)	-	-	1.2	金属 加 工 设 备	可逆式板坯机	-	2.5	2.5
	压滤器	1.0	1.3	1.5		可逆式线材机	-	1.8	1.8
	絮凝器	0.8	1.0	1.3		可逆式薄板机	-	2.0	2.0
	曝气机	-	1.8	2.0		可逆式中厚板机	-	1.8	1.8
	接集设备	1.0	1.2	1.3		辊缝调节驱动装置	0.9	1.0	-
	纵向、回转组合接集装置	1.0	1.3	1.5		斗式输送机	-	1.2	1.5
	预浓缩器	-	1.1	1.3		绞车	1.4	1.6	1.6
	螺杆泵	-	1.3	1.5		卷扬机	-	1.5	1.8
	水轮机	-	-	2.0		皮带输送机<150kw	1.0	1.2	1.3
	离心泵	1.0	1.2	1.3		皮带输送机≥150kw	1.1	1.3	1.5
挖泥机	1个活塞容积式泵	1.3	1.4	1.8		货用电梯*	-	1.2	1.5
	>1个活塞容积式泵	1.2	1.4	1.5		客用电梯*	-	1.5	1.8
	斗式运输机	-	1.6	1.6		刮板式输送机	-	1.2	1.5
	倾卸装置	-	1.3	1.5		自动扶梯	-	1.2	1.4
	Carteypillar行走机构	1.2	1.6	1.8		轨道行走机构	-	1.5	-
	斗轮式挖掘机(用于捡拾)	-	1.7	1.7		变频装置	-	1.8	2.0
	斗轮式挖掘机(用于粗料)	-	2.2	2.2		往复式压缩机	-	1.8	1.9
	切碎机	-	2.2	2.2	起重 机 械	回转机构	2.5	2.5	3.0
	行走机构*	-	1.4	1.8		俯仰机构	2.5	2.5	3.0
	弯板机*	-	1.0	1.0		行走机构	2.5	3.0	3.0
化 学 工 业	挤压机	-	-	1.6		提升机构	2.5	2.5	3.0
	调浆机	-	1.8	1.8		转臂式起重机	2.5	2.5	3.0
	橡胶研光机	-	1.5	1.5		冷却塔风扇	-	-	2.0
	冷却圆筒	-	1.3	1.4		风机(轴流和离心式)	-	1.4	1.5
	混料机,用于均匀介质	1.0	1.3	1.4	蔗 糖 生 产	甘蔗切碎机*	-	-	1.7
	混料机,用于非均匀介质	1.4	1.6	1.7		甘蔗碾磨机	-	-	1.7
	搅拌机,用于密度均匀介质	1.0	1.3	1.5		甜菜绞碎机	-	-	1.2
	搅拌机,用于非均匀介质	1.2	1.4	1.6		榨取机,机械致冷机,蒸煮机	-	-	1.4
	搅拌机,用于不均匀气体吸收	1.4	1.6	1.8		甜菜清洗机	-	-	1.5
金 属 加 工 设 备	烘炉	1.0	1.3	1.5		甜菜切碎机	-	-	1.5
	离心机	1.0	1.2	1.3	造 纸 机 械	各种类型**	-	1.8	2.0
	翻板机	1.0	1.0	1.2		碎浆机驱动装置	2.0	2.0	2.0
	推钢机	1.0	1.2	1.2		离心式压缩机	-	1.4	1.5
	绕线机	-	1.6	1.6		运货索道	-	1.3	1.4
	冷床横移架	-	1.5	1.5		往返系统空中索道	-	1.6	1.8
	辊式矫直机	-	1.6	1.6		T型杆升降机	-	1.3	1.4
	辊道(连续式)	-	1.5	1.5		连续索道	-	1.4	1.6
	辊道(间歇式)	-	2.0	2.0		混凝土搅拌器	-	1.5	1.5
	可逆式轧管机	-	1.8	1.8		破碎机*	-	1.2	1.4
金 属 加 工 设 备	剪切机(连续式)*	-	1.5	1.5		回转窑	-	-	2.0
	剪切机(曲柄式)*	1.0	1.0	1.0		管式磨机	-	-	2.0
	连铸机驱动装置	-	1.4	1.4		选粉机	-	1.6	1.6
	可逆式开坯机	-	2.5	2.5		辊压机	-	-	2.0

工作机额定功率P2的确定 *)按最大扭矩确定额定功率。 **)检验热功率是绝对必要的。

表 2

原动机系数

f2

电机,液压马达,汽轮机	1.0
4~6缸活塞发动机	1.25
1~3缸活塞发动机	1.5

表 4

环境温度工作系数

f4

环境温度℃	20℃	30℃	40℃	50℃
f4	1	1.15	1.35	1.65

表 3

起动系数

f3

f3	f1×f2	1	1.25 ~1.75	2~ 2.75	≥3
每小时起动次数					
≤5	1	1	1	1	1
6~25	1.2	1.12	1.06	1	
26~60	1.3	1.2	1.12	1.06	
61~180	1.5	1.3	1.2	1.12	
>180	1.7	1.5	1.3	1.2	



Gear Units Service Factor

Table 1

Factor for driven machine

f1

Driven machines		Effective daily operating period under load in hours			Driven machines		Effective daily operating period under load in hours		
		≤ 0.5h	0.5~10h	> 10h			≤ 0.5h	0.5~10h	> 10h
Waste water treatment	Thickeners(central drive)	-	-	1.2	Metal working mills	Reversing slabbing mills	-	2.5	2.5
	Filter presses	1.0	1.3	1.5		Reversing wire mills	-	1.8	1.8
	Flocculation apparatus	0.8	1.0	1.3		Reversing sheet mills	-	2.0	2.0
	Aerators	-	1.8	2.0		Reversing plate mills	-	1.8	1.8
	Raking equipment	1.0	1.2	1.3		Roll adjustment drives	0.9	1.0	-
	Combined longitudinal and rotary rakes	1.0	1.3	1.5	Conveyors	Bucket conveyors	-	1.2	1.5
	Pre-thickeners	-	1.1	1.3		Hauling winches	1.4	1.6	1.6
	Screw pumps	-	1.3	1.5		Hoists	-	1.5	1.8
	Water turbines	-	-	2.0		Belt conveyors <150 kw	1.0	1.2	1.3
	Centrifugal pumps	1.0	1.2	1.3		Belt conveyors ≥150 kw	1.1	1.3	1.5
Dredgers	1-piston positive-displacement pumps	1.3	1.4	1.8	Frequency converters	Goods lifts *	-	1.2	1.5
	>1-piston positive-displacement pumps	1.2	1.4	1.5		Passenger lifts *	-	1.5	1.8
	Bucket conveyors	-	1.6	1.6		Apron conveyors	-	1.2	1.5
	Dumping devices	-	1.3	1.5		Escalators	-	1.2	1.4
	Caterpillar travelling gears	1.2	1.6	1.8		Rail travelling gears	-	1.5	-
	Bucket wheel excavators as pick-up	-	1.7	1.7	Reciprocating compressors	Frequency converters	-	1.8	2.0
	Bucket wheel excavators for primitive material	-	2.2	2.2		Reciprocating compressors	-	1.8	1.9
Chemical Industry	Cutter heads	-	2.2	2.2		Slewing gears	2.5	2.5	3.0
	Traversing gears *	-	1.4	1.8		Luffing gears	2.5	2.5	3.0
	Plate bending machines *	-	1.0	1.0		Travelling gears	2.5	3.0	3.0
	Extruders	-	-	1.6		Hoisting gears	2.5	2.5	3.0
	Dough mills	-	1.8	1.8	Cranes	Derrick jib cranes	2.5	2.5	3.0
	Rubber calenders	-	1.5	1.5		Cooling tower fans	-	-	2.0
	Cooling drums	-	1.3	1.4		Blowers(axial and radial)	-	1.4	1.5
	Mixers for uniform media	1.0	1.3	1.4		Cane knives *	-	-	1.7
	Mixers for non-uniform media	1.4	1.6	1.7		Cane mills	-	-	1.7
Metal working mills	Agitators for media with uniform density	1.0	1.3	1.5	Cane sugar production	Beet cossettes macerators	-	-	1.2
	Agitators for media with non-uniform density	1.2	1.4	1.6		Extraction plants,Mechanical refrigerators,Juice boilers,	-	-	1.4
	Agitators for media with non-uniform gas absorption	1.4	1.6	1.8		Sugar beet washing machines	-	-	1.5
	Toasters	1.0	1.3	1.5		Sugar beet cutters	-	-	1.5
	Centrifuges	1.0	1.2	1.3		Paper machines	Of all-kind **	1.8	2.0
	Plate filters	1.0	1.0	1.2		Pulper drives	2.0	2.0	2.0
	Ingot pushers	1.0	1.2	1.2		Centrifugal compressors	-	1.4	1.5
	Winding machines	-	1.6	1.6		Material ropeways	-	1.3	1.4
	Cooling bed transfer frames	-	1.5	1.5		To-and-fro system aerial ropeways	-	1.6	1.8
	Roller straighteners	-	1.6	1.6		T-bar lifts	-	1.3	1.4
Cableways	Roller tables continuous	-	1.5	1.5		Continuous ropeways	-	1.4	1.6
	Roller tables intermittent	-	2.0	2.0	Cement industry	Concrete mixers	-	1.5	1.5
	Roller tables Reversing tube mills	-	1.8	1.8		Breakers *	-	1.2	1.4
	Shears continuous *	-	1.5	1.5		Rotary kilns	-	-	2.0
	Shears crank type *	1.0	1.0	1.0		Tube mills	-	-	2.0
	Continuous casting drivers	-	1.4	1.4		Separators	-	1.6	1.6
	Reversing blooming mills	-	2.5	2.5		Roll crushers	-	-	2.0

Design for power rating of driven machine P2 *)Designed power corresponding to max.torque.

**)A check for thermal capacity is absolutely essential.

Table 2 Factor for prime mover f2

Electric motors,hydraulic motors,turbines	1.0
Piston engines 4~6 cylinders	1.25
Piston engines 1~3 cylinders	1.5

Table 4 Ambient temperature work factor f4

Ambient temperature(℃)	20	30	40	50
f4	1	1.15	1.35	1.65

Table 3 Start factor f3

f3	f1×f2	1	1.25 ~1.75	2~ 2.75	≥ 3
Starts per hour					
≤ 5	1	1	1	1	1
6~25	1.2	1.12	1.06	1	
26~60	1.3	1.2	1.12	1.06	
61~180	1.5	1.3	1.2	1.12	
>180	1.7	1.5	1.3	1.2	

注意事项：

- 样本中的结构图和外形附图只属范例，并不要求严格一致；若需严格的外形及尺寸可向我们索取您所选定型号规格的CAD光盘。
- 样本中外形尺寸单位全部是毫米 (mm)。
- 所注重量和油量仅为平均值，并不要求严格一致。
- 传动能力表中只有4、6、8极电机的平均或同步转速值，准确的输出转速应以电机额定转速或输入转速除以精确或实际减速比。尺寸图表中的电机尺寸以所配电机规格确定。电机接线盒位置若有要求，订货时需标注确认。电机代号见附录部分。
- 为防止发生事故，所有旋转部件均应根据国家和当地安全规定加防护罩。
- 传动箱供货时带径向油封，其它要求另行说明。
- 传动箱供货时，铸件外表喷涂兰色或灰色油漆，铝合金外表喷涂银白色平面漆，要求其它色彩或特种油漆需注明。
- 通气帽、放油孔、油镜或油尺位置出厂时按公司图纸标准，指定位置订货时必需另行说明。
- 本说明书中的所有减速机都可以正反运转（除配单向逆止器外），书中只表示一个输入旋转方向；另一个旋转方向输入时，输出方向也将改变。输出轴的旋转方向与内部结构和输入旋转方向有关，斜齿轮与减速级有关，螺旋锥齿轮与相对装配位置有关，蜗轮箱与蜗杆螺旋旋转方向有关。
- 试车之前，必需认真阅读使用说明书。
- 传动箱供货时已作好运行准备，只是未加入润滑油。
- 减速机空心轴带收缩盘、花键轴、电机座和伺服电机联接法兰及逆止器，带强制风扇、润滑冷却及控制部分等装置另行咨询。
- 本选型手册仅提供标准产品内容，行业专用或特殊规格另行咨询。
- 传动能力表中有关最大允许直联电机功率是相对于4极电机的功率。

Notes:


- Structure drawings and outline pictures attached in this catalog are regarded as examples with no strict accordance with products. The exact CAD drawing and dimension of certain types can be offered.
- The unit of dimension is millimeter (mm).
- Labeled weight and oil capacity are not exact but average.
- There are only average speed of 4, 6, 8 pole motor in transmission capacity table, exact speed is motor speed divided by exact ration. Motor size in dimension table is determined by motor type. Special requirements on terminal box of motor should be specified when placing an order. Motor types can be referred to Appendix.
- To avoid accident, all rotative components must be installed dust hood complying with national and regional safety regulations.
- Charge-free radial seals will be added on delivery, please state if other requirements.
- Iron-cast surface is sprayed blue or gray paint, Aluminum-die-cast surface silver. Other colors or special lacquer will be specified.
- Location of breather valve, oil drain plug, oil level plug and oil dipstick is subject to our drawings of different types. Special requirement will be stated when ordering.
- All reducers can rotate on both opposite directions (except installation of backstop) in this catalog, and only one input direction is marked, the input direction changed into the opposite will cause the change of output direction. The output direction relates to inner structure and input direction, to number of stages of helical gears, to relative position of spiral gears, to the rotation direction of worm in worm gear units.
- Please read the catalog before running the reducer.
- Gear units have been debugged, but lubrication will be added before running.
- Shrink disk, involute spline, motor base, flange and backstop connected with servo motor, cooling fan, lubrication cooling and controller will be specified when needed. We will offer reference.
- Please consult us for special products because all information in this catalog is subject to general standards.
- Maximum motor power in transmission capacity table is of 4-pole electric motor.

**代号说明****SYMBOL SPECIFICATION**

代号 Symbol	说 明	Specification	单 位 Unit
i	实际减速比	Actual ratio	/
iN	公称减速比	Nominal ratio	
iex	精确减速比	Exact ratio	
T ₂	输出扭矩	Output torque	N·m
T _{2N}	额定输出扭矩	Rated output torque	
T _A	峰值扭矩	Max. Torque occurring on input shaft, e.g. Peak operating, starting or braking torque	
T _{n2atmax}	在最高转速时的额定输出扭矩	Nominal output torque at highest speed	/
T _{n2atmin}	在最低转速时的额定输出扭矩	Nominal output torque at lowest speed	
P _{1N}	减速机额定输入功率	Rated input power	
P _G	热容量功率	Thermal capacity power	kW
P ₁	输入功率	Input power	
P ₂	输出功率	Output power	
t	环境温度	Ambient temperature	℃
f ₁	被驱动设备系数	Driven machine factor	/
f ₂	原动机系数	Drives factor	
f _t	环境温度系数	Temperature factor	
n ₁	输入转速	Input speed	r/min
n _m	电机转速	Motor speed	
n _{2N}	公称输出转速	Nominal output speed	
n ₂	输出转速	Output speed	N
F _{r1}	输入轴额定径向力	Nominal radial force on input shaft	
F _{r2}	输出轴额定径向力	Nominal radial force on output shaft	
F _a	输出轴额定轴向力	Nominal axial force on output shaft	
η	效率	Efficiency	/
f	电机频率	Motor frequency	Hz
V _{mot}	电机电压	Motor voltage	V
V _{brake}	制动器电压	Braker voltage	



R 系列刚齿轮硬齿面减速机
R Rigid tooth flank helical gear units




R (RF, RX, RXF) ... Y...
电机用户自配或配特殊电机时
需加联接法兰


When equipping the user's motor or the
special one, the flange is required to be
connected

R系列减速机有以下设计方案：


R series gear units are available in the following designs:




R...Y...
底脚轴伸式安装斜齿轮减速机
Foot-mounted helical gear units with solid shaft




RF...Y...
法兰轴伸式安装斜齿轮减速机
Flange-mounted helical gear units with solid shaft




RS...
底脚轴伸式安装，轴输入的斜齿轮减速机
Foot-mounted, shaft input helical gear units with solid shaft




RFS...
法兰轴伸式，轴输入的斜齿轮减速机
Flange-mounted, shaft input helical gear units with solid shaft




R...R...Y...
底脚轴伸式安装组合型斜齿轮减速机
Foot-mounted combinatorial helical gear units with solid shaft




RF...R...Y...
法兰轴伸式组合型斜齿轮减速机
Flange-mounted combinatorial helical gear units with solid shaft




RS...R...
底脚轴伸式安装组合型，轴输入的
斜齿轮减速机
Foot-mounted combinatorial, shaft input helical gear units with solid shaft




RFS...R...
法兰轴伸式组合型，轴输入的
斜齿轮减速机
Flange-mounted combinatorial, shaft input helical gear units with solid shaft




RX...Y...
底脚轴伸式安装单级斜齿轮减速机
Foot-mounted single-stage helical gear units with solid shaft



RXF...Y...
法兰轴伸式安装单级斜齿轮减速机
Flange-mounted single-stage helical gear units with solid shaft



RXS...
底脚轴伸式安装，轴输入的单级
斜齿轮减速机
Foot-mounted, shaft input single-stage helical gear units with solid shaft



RXFS...
法兰轴伸式，轴输入的单级斜齿轮减速机
Flange-mounted, shaft input single-stage helical gear units with solid shaft

R

**型号与标记:**

Type Designations:


R F 37-Y 0.55-4P-32.40-M1-270°-Φ200	R F 37-Y 0.55-4P-32.40-M1-270°-Φ200
减速机类型	Gear units type
结构形式	Structure
规格	Size
电机代号	Motor code
电机功率、极数	Motor power, pole
传动比	Ratio
安装形式	Mounting position
电机接线盒位置	Position of the motor thermal box
输出法兰外径	Outer diameter of output flange

R


减速机类型: 斜齿轮硬齿面减速机	Gear units type: rigid tooth flank helical gear units
结构形式: 普通轴伸式(省略) 轴伸法兰式 F 普通轴伸式, 轴输入 S 轴伸法兰式, 轴输入 FS	Structure: Foot-mounted solid shaft output (-) Flange-mounted solid shaft output F Foot-mounted solid shaft output, shaft input S Flange-mounted solid shaft output, shaft input FS
规格: (见选型参数表)	Size: (see selection table)
电机代号: 普通(更新) Y(Y2) 防爆 B 直流 Z 制动 YEJ 多速 D 变频 YVP 电磁调速 YCT 冶金起重 R 变频制动 YVPJ 辊道 G	Motor code: Ordinary(renew) Y(Y2) Flame-proof B Direct current Z Brake YEJ Multi-speed D Variable frequency YVP Electromagnetism speed modulation YCT Hoisting in metallurgy R Variable frequency and brake YVPJ Roller tables G
电机功率、极数: (见选型参数表)	Motor power, pole : (see selection table)
传动比: (见选型参数表)	Ratio: (see selection table)
安装形式: M1、M2、M3、M4、M5、M6(见第9页)	Mounting position: M1、M2、M3、M4、M5、M6(see page 9)
电机接线盒位置: 0°、90°、180°、270°(见第8页)	Position of the motor thermal box: 0°、90°、180°、270° (see page 8)
输出法兰外径: (见外型安装尺寸图)底脚安装时省略	Outer diameter of output flange: (See the chart of mounting dimension sheets-overview) It will be omitted when foot mounting.

电机接线盒位置:


Position of the motor thermal box:




0°



90°



180°




270°



安装形式:

Mounting position:



R

输入功率及许用转矩

Input power rating and permissible torque

规格 Size	17	27	37	47	57	67	77	87	97	107	137	147	167
结构形式 Structure	R RF												
输入功率 Input power rating (kW)	0.18~0.75	0.18~3	0.18~3	0.18~5.5	0.18~7.5	0.18~7.5	0.18~11	0.55~22	0.55~30	2.2~45	5.5~55	11~90	11~160
传动比 Ratio	3.83~ 74.84	3.37~ 135.09	3.33~ 134.82	3.83~ 176.88	4.39~ 186.89	4.29~ 199.81	5.21~ 195.24	5.36~ 246.54	4.49~ 289.74	5.06~ 249.16	5.15~ 222.60	5.00~ 163.31	10.24~ 229.71
许用转矩 Permissible torque (N.m)	85	130	200	300	450	600	820	1550	3000	4300	8000	13000	18000

规格 Size	37	57	67	77	87	97	107	127	157
结构形式 Structure	RX RXF								
输入功率(kW) Input power rating	0.18~1.1	0.18~5.5	0.18~7.5	1.1~11	3~22	5.5~30	7.5~45	7.5~90	11~132
传动比 Ratio	1.62~4.43	1.3~5.5	1.4~6.07	1.42~8.00	1.39~8.65	1.42~8.23	1.44~6.63	1.51~6.2	1.57~6.2
许用转矩 (N.m) Permissible torque	20	70	135	215	400	600	830	1110	1680


减速机重量

Gear unit weight

规格 Size	R17	R27	R37	R47	R57	R67	R77	R87	R97	R107	R137	R147	R167
重量(kg) Weight	4	5.5	8.5	10	18	25	36	63	101	153	220	400	700
机型号 Gear unit type	RX37	RX57	RX67	RX77	RX87	RX97	RX107	RX127	RX157				
重量(kg) Weight	5	8	14	23	39	70	100	150	250				

所注重量为平均值，仅供参考

The weights are mean values, only for reference.



润滑油量表

Lubrication table

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1 ¹⁾	M2 ¹⁾	M3	M4	M5	M6
R17	0.25	0.6	0.35	0.6	0.35	0.35
R27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
R37	0.3/1	0.9	1	1.1	0.8	1
R47	0.7/1.5	1.6	1.5	1.7	1.5	1.5
R57	0.8/1.7	1.9	1.7	2.1	1.7	1.7
R67	1.1/2.3	2.6/3.5	2.8	3.2	1.8	2
R77	1.2/3	3.8/4.3	3.6	4.3	2.5	3.4
R87	2.3/6	6.7/8.4	7.2	7.7	6.3	6.5
R97	4.6/9.8	11.7/14	11.7	13.4	11.3	11.7
R107	6/13.7	16.3	16.9	19.2	13.2	15.9
R137	10/25	28	29.5	31.5	25	25
R147	15.4/40	46.5	48	52	39.5	41
R167	27/70	82	78	88	66	69

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1 ¹⁾	M2 ¹⁾	M3	M4	M5	M6
RF17	0.25	0.6	0.35	0.6	0.35	0.35
RF27	0.25/0.4	0.7	0.4	0.7	0.4	0.4
RF37	0.4/1	0.9	1	1.1	0.8	1
RF47	0.75/1.5	1.6	1.5	1.7	1.5	1.5
RF57	0.8/1.7	1.8	1.7	2	1.7	1.7
RF67	1.2/2.5	2.7/3.6	2.7	3.1	1.9	2.1
RF77	1.2/2.6	3.8/4.1	3.3	4.1	2.4	3
RF87	2.4/6	6.8/7.9	7.1	7.7	6.3	6.4
RF97	5.1/10.2	11.9/14	11.2	14	11.2	11.8
RF107	6.3/14.9	15.9	17	19.2	13.1	15.9
RF137	9.5/25	27	29	32.5	25	25
RF147	16.4/42	47	48	52	42	42
RF167	26/70	82	78	88	65	71

规格 Size	润滑油量(升)			Fill quantity in liters		
	M1	M2	M3	M4	M5	M6
RX37/RXF37	0.45/0.4	0.6	1.1/0.9	1.1/0.9	0.7/0.6	0.7/0.6
RX57/RXF57	0.6/0.5	0.8	1.3/1.1	1.3/1.1	0.9/0.7	0.9/0.7
RX67/RXF67	0.8/0.7	0.8	1.7/1.5	1.9/1.7	1.1/1	1.1/1
RX77/RXF77	1.1/0.9	1.5	2.6/2.4	2.7/2.5	1.6	1.6
RX87/RXF87	1.7/1.6	2.5	4.8/4.9	4.8/4.7	2.9	2.9
RX97/RXF97	2.1	3.4/3.6	7.4/7.1	7	4.8	4.8
RX107/RXF107	3.9/3.1	5.6/5.9	11.6/11.2	11.9/10.5	7.7/7.2	7.7/7.2
RX127/RXF127	5.6/5.9	11.6/11.2	21.9/20.5	22.7/22.2	9.7/9.2	9.7/9.2
RX157/RXF157	11.6/11.2	21.9/20.5	31.3/30.5	32.7/32.2	13.2/12.7	13.2/12.7

注：1) 表示减速机为组合型时低速级所加油量为大值。

Notes: 1)The large gear unit of multi-stage gear units must be filled with the larger oil volume.



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
0.18kW											
0.16	9293	8443	1.31			1.6	944	858	0.82		
0.19	8042	7307	1.52			1.7	904	821	0.85		
0.22	7096	6447	1.72	R 147R77	4	1.8	833	757	0.93		
0.25	6128	5568	1.99	RF147R77	4	1.9	803	730	0.96		
0.29	5300	4815	2.31			2.1	739	671	1.04		
0.32	4760	4325	2.57			2.2	711	646	1.08	R 77R37	4
0.38	4038	3669	3.03			2.4	628	571	1.23	RF77R37	4
0.43	3553	3228	3.44			2.5	602	547	1.28		
						2.9	525	477	1.47		
0.16	9668	8784	0.8			3.3	469	426	1.64		
0.19	8232	7479	0.91			3.8	402	365	1.92		
0.22	7057	6412	1.07	R 137R77	4	4.5	341	310	2.26		
0.24	6421	5834	1.17	RF137R77	4	2.4	628	571	0.90		
0.28	5504	5001	1.37			2.5	617	561	0.91		
0.30	5183	4709	1.45			2.9	532	483	1.06		
0.32	4803	4364	1.57			3.2	482	438	1.17	R 67R37	4
0.35	4323	3928	1.74			3.6	427	388	1.32	RF67R37	4
0.40	3868	3514	1.94			4.1	370	336	1.53		
0.42	3674	3338	2.05			4.8	316	287	1.79		
0.47	3224	2929	2.33			5.5	281	255	2.01		
0.31	4881	4435	0.83			3.0	518	471	0.82		
0.36	4260	3870	0.95			3.1	488	443	0.87		
0.42	3634	3302	1.11			3.4	451	410	0.94		
0.46	3299	2997	1.23			3.9	395	359	1.07		
0.53	2885	2621	1.40			4.3	357	324	1.19		
0.62	2479	2252	1.63	R 107R77	4	4.4	351	319	1.20		
0.68	2246	2041	1.80	RF107R77	4	4.8	319	290	1.33	R 57R37	4
0.71	2169	1971	1.86			5.2	294	267	1.44	RF57R37	4
0.77	1995	1813	2.03			5.3	288	262	1.47		
0.88	1747	1587	2.31			5.7	271	246	1.56		
1.0	1529	1389	2.64			5.8	265	241	1.59		
1.1	1338	1216	3.02			6.3	242	220	1.75		
						6.5	237	215	1.79		
						7.4	207	188	2.04		
0.51	2996	2722	0.94			8.7	175	159	2.42		
0.52	2937	2668	0.96			4.6	331	301	0.85		
0.60	2544	2311	1.11			5.5	281	255	1.00	R 47R37	4
0.62	2471	2245	1.14			6.1	251	228	1.12	RF47R37	4
0.67	2287	2078	1.23			7.1	215	195	1.31		
0.69	2219	2016	1.27			6.2	249	226	0.8		
0.80	1907	1733	1.48	R 97R57	4	6.9	222	202	0.85		
0.86	1786	1623	1.58	RF97R57	4	7.0	219	199	0.86		
0.97	1578	1434	1.79			7.8	197	179	0.95	R 37R17	4
1.2	1328	1207	2.12			8.9	173	157	1.09	RF37R17	4
1.3	1193	1084	2.36			9.1	172	156	1.11		
1.5	1028	934	2.74			9.3	165	150	1.14		
1.6	966	878	2.92			9.9	155	141	0.8		
1.8	831	755	3.39			10	149	135	0.82		
						11	136	124	0.90	R 27R17	4
0.79	1912	1737	0.8			12	130	118	0.94	RF27R17	4
0.80	1907	1733	0.85			13	121	110	1.01		
0.91	1677	1524	0.87			14	114	104	1.07		
0.93	1639	1489	0.89			15	103	94	1.18		
1.0	1535	1395	0.95			4.4	371	195.24	2.1		
1.1	1356	1232	1.07	R 87R57	4	5.1	317	166.59	2.4		
1.2	1260	1145	1.16	RF87R57	4	5.8	277	145.67	2.8	R 77	6
1.3	1141	1037	1.28			6.1	263	138.39	2.9	RF77	6
1.5	1025	931	1.42			7.0	231	121.42	3.3		
1.6	972	883	1.50								
1.7	883	802	1.65								
1.8	852	774	1.71								

R



造型参数表
Selection Table

R

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type						极数 Pole					
0.18kW						0.18kW																													
7.1	227	195.24	3.4																																
8.3	194	166.59	4.0	R	77	4																													
9.5	169	145.67	4.6	RF	77	4																													
10	161	138.39	4.8																																
4.3	380	199.81	1.48																																
4.6	350	184.07	1.61																																
5.4	301	158.14	1.88																																
6.2	262	137.67	2.2																																
6.6	245	128.97	2.3	R	67	6																													
7.5	217	113.94	2.6	RF	67	6																													
8.0	201	105.83	2.8																																
8.9	182	95.91	3.1																																
9.9	164	86.11	3.4																																
11	141	74.17	4.0																																
12	133	69.75	4.3																																
7.0	232	199.81	2.4																																
7.6	214	184.07	2.6																																
8.8	184	158.14	3.1																																
10	160	137.67	3.5	R	67	4																													
11	150	128.97	3.8	RF	67	4																													
12	132	113.94	4.3																																
13	123	105.83	4.6																																
4.5	355	186.89	1.19																																
4.9	327	172.17	1.29	R	57	6																													
5.7	281	147.92	1.50	RF	57	6																													
6.6	245	128.77	1.73																																
7.0	229	120.63	1.84																																
7.4	217	186.89	1.95																																
8.1	200	172.17	2.1																																
9.4	172	147.92	2.5																																
11	150	128.77	2.8	R	57	4																													
12	140	120.63	3.0	RF	57	4																													
13	124	106.58	3.4																																
14	115	98.99	3.7																																
15	104	89.71	4.1																																
7.9	206	176.88	1.37																																
8.5	189	162.94	1.49																																
9.9	163	139.99	1.73																																
11	142	121.87	1.99																																
12	133	114.17	2.1	R	47	4																													
14	117	100.86	2.4	RF	47	4																													
15	109	93.68	2.6																																
16	99	84.90	2.9																																
18	89	76.23	3.2																																
6.9	235	123.66	0.80																																
8.1	200	105.28	0.94	R	37	6																													
9.4	173	90.77	1.09	RF	37	6																													
10	161	84.61	1.17																																
10	157	134.82	1.20																																
11	144	123.66	1.31																																
13	122	105.28	1.54																																
15	106	90.77	1.78																																
16	98	84.61	1.91	R	37	4																													
19	86	73.96	2.2	RF	37	4																													
20	81	69.33	2.3																																
23	71	61.18	2.6																																
25	65	55.76	2.9																																
29	56	48.08	3.1																																

造型参数表
 Selection Table


输出转速	输出扭矩	传动比	使用系数	机型号	极数	输出转速	输出扭矩	传动比	使用系数	机型号	极数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
0.18kW						0.25kW					
229	7.4	6.07	5.5			0.69	3082	2016	0.92		
268	6.3	5.18	11			0.76	2787	1823	1.01		
307	5.5	4.53	13			0.80	2649	1733	1.06		
323	5.2	4.30	14			0.86	2481	1623	1.14		
369	4.6	3.77	18	RX 67	4	0.88	2420	1583	1.17	R 97R57	4
434	3.9	3.20	24	RXF67	4	1.0	2134	1396	1.32	RF97R57	4
481	3.5	2.89	28			1.1	1877	1228	1.50		
547	3.1	2.54	36			1.3	1633	1068	1.73		
579	2.9	2.40	40			1.5	1432	937	1.97		
681	2.5	2.04	51			1.7	1260	824	2.2		
						1.9	1127	737	2.5		
155	11	5.50	3.36			2.2	965	631	2.9		
168	10	5.07	3.37	RX 57	6						
195	8.6	4.35	7.4	RXF57	6	1.2	1750	1145	0.83		
224	7.5	3.79	8.5			1.3	1585	1037	0.92		
253	6.7	5.50	5.50			1.5	1423	931	1.02		
274	6.1	5.07	5.51			1.6	1350	883	1.08		
320	5.3	4.35	12			1.7	1226	802	1.19		
367	4.6	3.79	14			1.8	1183	774	1.23	R 87R57	4
392	4.3	3.55	15			2.0	1044	683	1.40	RF87R57	4
443	3.8	3.14	16	RX 57	4	2.3	916	599	1.59		
478	3.5	2.91	18	RXF57	4	2.6	803	525	1.82		
527	3.2	2.64	20			3.1	694	454	2.1		
586	2.9	2.37	23			5.2	408	267	3.6		
681	2.5	2.04	26								
724	2.3	1.92	28			2.4	873	571	0.88		
842	2.0	1.65	32			2.5	836	547	0.92		
426	4	3.26	3.80	RX 37	4	2.9	729	477	1.06		
527	3	2.64	4.69	RXF37	4	3.3	651	426	1.18	R 77R37	4
0.25kW						3.8	556	364	1.39	RF77R37	4
0.14	14894	9743	0.82			4.3	507	327	1.52		
0.16	12907	8443	0.95			4.6	474	310	1.63		
0.19	11170	7307	1.09			5.6	379	248	2.03		
0.22	9855	6447	1.24	R 147R77	4	6.3	335	219	2.3		
0.25	8512	5568	1.44	RF147R77	4						
0.29	7361	4815	1.66			3.6	593	388	0.95		
0.32	6612	4325	1.85			3.9	549	359	1.03		
0.38	5609	3669	2.18			4.1	514	336	1.10		
0.43	4935	3228	2.48			4.5	474	310	1.19		
0.49	4331	2833	2.82			4.8	439	287	1.29		
0.24	8918	5834	0.84			5.3	404	264	1.40		
0.28	7645	5001	0.98			5.5	390	255	1.45	R 67R37	4
0.30	7199	4709	1.04			5.9	359	235	1.57	RF67R37	4
0.32	6671	4364	1.13			6.1	350	229	1.61		
0.35	6142	4018	1.22			6.9	307	201	1.84		
0.37	6005	3928	1.25	R 137R77	4	7.1	298	195	1.89		
0.40	5372	3514	1.40	RF137R77	4	7.7	277	181	2.0		
0.42	5103	3338	1.47			8.1	263	172	2.15		
0.47	4478	2929	1.68			9.0	235	154	2.40		
0.52	4063	2658	1.85								
0.58	3687	2414	2.0			4.3	495	324	0.85		
0.67	3169	2073	2.4			4.4	488	319	0.87		
0.76	2811	1839	2.7			4.8	443	290	0.95		
0.99	2136	1397	3.5			5.2	408	267	1.04		
1.1	1874	1226	4.0			5.3	401	262	1.06		
0.71	3013	1971	1.34			5.7	376	246	1.12	R 57R37	4
0.77	2772	1813	1.46			5.8	368	241	1.15	RF57R37	4
0.88	2426	1587	1.67	R 107R77	4	6.3	336	220	1.26		
1.0	2123	1389	1.90	RF107R77	4	6.5	329	215	1.29		
1.1	1859	1216	2.2			7.6	280	183	1.51		
1.5	1417	927	2.9			8.6	246	161	1.72		
1.7	1241	812	3.3			10	211	138	2.0		

R



造型參數表

输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
0.25kW											
8.9	238	156	0.79			7.4	308	186.89	1.37		
9.3	229	150	0.82			8.1	284	172.17	1.49		
10	206	135	0.91	R 37R17	4	9.4	244	147.92	1.73		
11	194	127	0.97	R 37R17	4	11	212	128.77	1.99	R 57	4
12	168	110	1.12	RF37R17	4	12	199	120.63	2.1	RF57	4
13	159	104	1.18			13	176	106.58	2.4		
14	144	94	1.31			14	163	98.99	2.6		
15	138	90	1.37			15	148	89.71	2.9		
						17	133	80.55	3.2		
						20	114	69.23	3.7		
2.2	1029	289.60	2.7			7.9	292	176.88	0.97		
2.5	913	256.89	3.1	R 97	8	8.5	269	162.94	1.05		
2.7	856	240.83	3.3	RF97	8	9.9	231	139.99	1.22		
3.0	767	215.94	3.7			11	201	121.87	1.40		
						12	188	114.17	1.50		
2.6	876	246.54	1.66			14	166	100.86	1.70	R 47	4
3.0	769	216.54	1.89	R 87	8	15	154	93.68	1.83	RF47	4
3.1	731	205.71	1.99	RF87	8	16	140	84.90	2.0		
3.5	646	181.77	2.3			18	126	76.23	2.2		
						20	113	68.54	2.5		
3.9	592	166.59	1.30			22	106	64.21	2.7		
4.4	518	145.67	1.49	R 77	8	25	94	56.73	3.0		
4.7	492	138.39	1.57	RF77	8	26	87	52.69	3.2		
5.3	431	121.42	1.79			29	79	47.75	3.6		
4.4	526	195.24	1.46	R 77	6	10	222	134.82	0.85		
5.1	449	166.59	1.72	RF77	6	11	204	123.66	0.92		
5.8	393	145.67	1.96			13	175	105.28	1.08		
						15	150	90.77	1.26		
7.1	322	195.24	2.4			16	140	84.61	1.35		
8.3	275	166.59	2.8	R 77	4	19	122	73.96	1.54	R 37	4
9.5	240	145.67	3.2	RF77	4	20	114	69.33	1.64	RF37	4
10	228	138.39	3.4			23	101	61.18	1.86		
11	200	121.42	3.8			25	92	55.76	2.0		
						29	79	48.08	2.4		
4.1	562	158.14	1.00			31	74	44.81	2.5		
4.7	489	137.67	1.15	R 67	8	35	65	39.17	2.9		
5.0	458	128.97	1.23	RF67	8	38	61	36.72	3.1		
5.7	405	113.94	1.39			43	53	32.40	3.5		
4.3	539	199.81	1.05			16	140	84.78	0.87		
4.6	496	184.07	1.14			19	122	74.11	1.00		
5.4	426	158.14	1.32	R 67	6	20	115	69.47	1.07		
6.2	371	137.67	1.52	RF67	6	23	101	61.30	1.21		
6.6	348	128.97	1.62			25	92	55.87	1.33		
7.5	307	113.94	1.84			29	79	48.17	1.54		
8.0	285	105.83	1.98			31	74	44.90	1.65		
						35	65	39.25	1.89		
7.0	329	199.81	1.71			38	61	36.79	2.0		
7.6	304	184.07	1.86			43	54	32.47	2.3		
8.8	261	158.14	2.2			48	48	28.78	2.5		
10	227	137.67	2.5	R 67	4	49	47	28.37	2.6		
11	213	128.97	2.7	RF67	4	53	43	26.09	2.8		
12	188	113.94	3.0			57	40	24.47	3.0	R 27	4
13	175	105.83	3.2			62	37	22.32	3.3	RF27	4
14	158	95.91	3.6			72	32	19.35	3.8		
16	142	86.11	4.0			77	30	18.08	4.1		
						89	26	15.63	4.7		
4.5	504	186.89	0.84			105	22	13.28	5.6		
4.9	464	172.17	0.91			117	20	11.86	6.2		
5.7	399	147.92	1.06	R 57	6	137	17	10.13	6.9		
6.6	347	128.77	1.22	RF57	6	148	16	9.41	7.4		
7.0	325	120.63	1.30			170	14	8.16	8.1		
8.0	287	106.58	1.47			182	13	7.63	8.4		
8.6	267	98.99	1.58			211	11	6.59	9.2		
						248	9.0	5.60	10		
						278	8.2	5.00	11		
						326	7.0	4.27	12		
						348	7.0	4.00	12		
						412	6.0	3.37	13		


造型参数表
 Selection Table
 

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
0.25kW											
26	87	52.57	0.92			0.19	16532	7307	0.80		
28	81	49.28	0.98			0.22	14586	6447	0.84		
32	72	43.49	1.11			0.25	12597	5568	0.97		
34	67	40.49	1.20			0.29	10894	4815	1.12	R 147R77	4
39	58	35.40	1.37			0.32	9785	4325	1.25	RF147R77	4
42	55	33.18	1.46			0.38	8301	3669	1.47		
47	48	29.28	1.65			0.43	7303	3228	1.67		
54	43	25.96	1.87			0.49	6410	2833	1.91		
60	38	23.13	2.1								
63	36	22.06	2.2			0.32	9873	4364	0.76		
66	35	21.22	2.3			0.35	8887	3928	0.85		
77	30	18.06	2.7	R 17	4	0.40	7950	3514	0.95		
89	26	15.57	3.1	RF17	4	0.42	7552	3338	1.00		
96	24	14.52	3.3			0.47	6627	2929	1.13		
110	21	12.69	3.8			0.52	6014	2658	1.25		
117	20	11.89	4.1			0.56	5620	2484	1.34	R 137R77	4
132	17	10.5	4.2			0.58	5457	2412	1.38	RF137R77	4
149	15	9.31	4.4			0.62	5072	2242	1.48		
176	13	7.91	4.5			0.67	4690	2073	1.60		
184	12	7.55	4.7			0.76	4161	1839	1.81		
197	11	7.04	5.0			0.99	3161	1397	2.4		
226	10	6.15	5.2			1.1	2774	1226	2.7		
241	9	5.76	5.3			1.3	2466	1090	3.0		
273	8	5.09	5.7			1.5	2152	951	3.5		
308	7	4.51	6.1								
363	6	3.83	6.7			0.68	4618	2041	0.88		
140	16	6.07	2.5			0.71	4459	1971	0.91		
164	14	5.18	4.9	RX 67	6	0.77	4102	1813	0.99		
188	13	4.53	6.2	RXF67	6	0.83	3785	1673	1.07		
198	12	4.30	6.4			0.88	3591	1587	1.13	R 107R77	4
229	10	6.07	4.0			0.91	3464	1531	1.17	RF107R77	4
268	9	5.18	8.1			1.0	3145	1390	1.29		
307	8	4.53	10			1.1	2751	1216	1.47		
323	7	4.30	10			1.2	2701	1194	1.50		
369	6	3.77	13	RX 67	4	1.3	2360	1043	1.71		
434	5.5	3.20	17	RXF67	4	1.5	2097	927	1.93		
481	5	2.89	20			1.7	1837	812	2.2		
547	4.5	2.54	26								
579	4	2.40	29			0.97	3244	1434	0.87		
681	3	2.04	37			1.0	3158	1396	0.89		
155	15	5.50	2.4			1.1	2778	1228	1.02		
168	14	5.07	2.4	RX 57	6	1.2	2731	1207	1.03		
195	12	4.35	5.3	RXF57	6	1.3	2453	1084	1.15		
224	10	3.79	6.2			1.4	2416	1068	1.17	R 97R57	4
253	9.3	5.50	4.0			1.5	2120	937	1.33	RF97R57	4
274	8.5	5.07	4.0			1.7	1864	824	1.51		
320	7.3	4.35	9.0			1.9	1667	737	1.69		
367	6.4	3.79	10			2.2	1428	631	1.98		
392	6.0	3.55	11			3.2	973	430	2.9		
443	5.3	3.14	12	RX 57	4	3.7	857	379	3.3		
478	4.9	2.91	13	RXF57	4	4.1	760	336	3.7		
527	4.4	2.64	15								
586	4.0	2.37	16			1.7	1814	802	0.80		
681	3.4	2.04	19			1.8	1751	774	0.83		
724	3.2	1.92	20			1.9	1706	754	0.85		
842	2.8	1.65	23			2.0	1545	683	0.94		
370	6	3.76	2.37			2.1	1468	649	0.99		
426	5.5	3.26	2.73			2.3	1355	599	1.08		
456	5	3.05	2.92			2.5	1217	538	1.20	R 87R57	4
527	4.5	2.64	3.38	RX 37	4	2.6	1188	525	1.23	RF87R57	4
621	4	2.24	3.98	RXF37	4	2.9	1068	472	1.36		
695	3.5	2.00	4.46			3.1	1027	454	1.42		
813	3	1.71	5.21			3.5	905	400	1.61		
869	2.5	1.60	5.57			3.9	817	361	1.78		
						5.2	604	267	2.4		
						5.9	532	235	2.7		

R



造型参数表
Selection Table

R

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f _b						机型号 Type													
0.37kW						0.37kW																															
3.3	964	426	0.80			6.6	503	128.77	0.84																												
3.8	824	364	0.94			7.0	471	120.63	0.90	R	57	6																									
4.3	740	327	1.04			8.0	416	106.58	1.02	RF	57	6																									
4.5	701	310	1.10			8.6	387	98.99	1.09																												
5.6	561	248	1.37	R	77R37	4																															
6.3	495	219	1.56	RF	77R37	4																															
7.4	425	188	1.81				7.4	447	186.89	0.95																											
8.6	367	162	2.1				8.1	411	172.17	1.03																											
9.8	321	142	2.4				9.4	353	147.92	1.20																											
4.8	649	287	0.87				11	308	128.77	1.37																											
5.5	577	255	0.98	R	67R37	4																															
6.1	518	229	1.09	RF	67R37	4																															
7.1	441	195	1.28				12	288	120.63	1.47																											
2.5	1323	256.89	2.1				13	255	106.58	1.66	R	57	4																								
2.7	1240	240.83	2.3	R	97	8	14	237	98.99	1.79	RF	57	4																								
3.0	1112	215.94	2.5	RF	97	8	15	214	89.71	1.97																											
3.5	958	185.97	2.9				17	192	80.55	2.2																											
2.9	1132	289.60	2.5				20	165	69.23	2.6																											
3.3	1004	256.89	2.8	R	97	6	21	155	64.85	2.7																											
3.5	941	240.83	3.0	RF	97	6	24	137	57.29	3.1																											
3.9	844	215.94	3.3				26	127	53.22	3.3																											
3.0	1115	216.54	1.31	R	87	8	29	115	48.23	3.7																											
3.1	1059	205.71	1.38	RF	87	8																															
3.5	936	181.77	1.6																																		
3.4	963	246.54	1.51																																		
3.9	846	216.54	1.72																																		
4.1	804	205.71	1.81	R	87	6																															
4.7	710	181.77	2.1	RF	87	6																															
5.5	607	155.34	2.4																																		
6.0	556	142.41	2.6																																		
4.4	750	145.67	1.03																																		
4.7	713	138.39	1.08	R	77	8																															
5.3	625	121.42	1.23	RF	77	8																															
5.1	651	166.59	1.18																																		
5.8	569	145.67	1.35	R	77	6																															
6.1	541	138.39	1.43	RF	77	6																															
7.1	467	195.24	1.65																																		
8.3	398	166.59	1.94																																		
9.5	348	145.67	2.2	R	77	4																															
10	331	138.39	2.3	RF	77	4																															
11	290	121.42	2.7																																		
13	246	102.99	3.1																																		
15	222	92.97	3.47																																		
5.4	618	158.14	0.91																																		
6.2	538	137.67	1.05	R	67	6																															
6.6	504	128.97	1.12	RF	67	6																															
7.5	445	113.94	1.27																																		
7.0	477	199.81	1.18																																		
7.6	440	184.07	1.28																																		
8.8	378	158.14	1.49																																		
10	329	137.67	1.71																																		
11	308	128.97	1.83	R	67	4																															
12	272	113.94	2.1	RF	67	4																															
13	253	105.83	2.2																																		
14	229	95.91	2.5																																		
16	206	86.11	2.7																																		
19	177	74.17	3.2																																		
20	167	69.75	3.4																																		
23	146	61.26	3.9																																		
24	136	56.89	4.1																																		



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
0.37kW						0.37kW					
23	146	61.30	0.83			253	13.7	5.50	2.7		
25	134	55.87	0.92			274	12.6	5.07	2.7		
29	115	48.17	1.06			320	10.8	4.35	5.9		
31	107	44.90	1.14			367	9.4	3.79	6.9		
35	94	39.25	1.30			392	8.8	3.55	7.3		
38	88	36.79	1.39			443	7.8	3.14	7.8	RX 57	4
43	78	32.47	1.57	R 27	4	478	7.2	2.91	8.7	RXF57	4
48	69	28.78	1.78	RF27	4	527	6.6	2.64	9.9		
49	68	28.37	1.80			586	5.9	2.37	11		
53	62	26.09	1.96			681	5.1	2.04	13		
57	58	24.47	2.1			724	4.8	1.92	14		
62	53	22.32	2.3			842	4.1	1.65	16		
72	46	19.35	2.6								
77	43	18.08	2.8			426	8.1	3.26	1.85		
89	37	15.63	3.3			456	7.6	3.05	1.97		
105	32	13.28	3.9			527	6.6	2.64	2.28	RX 37	4
39	85	35.40	0.94			621	5.6	2.24	2.69	RXF37	4
42	79	33.18	1.01			695	5.0	2.00	3.01		
47	70	29.28	1.14			813	4.3	1.71	3.52		
54	62	25.96	1.29			869	4.0	1.60	3.76		
60	55	23.13	1.45								
63	53	22.06	1.52			0.55kW					
66	51	21.22	1.58			0.23	20411	6069	0.83		
77	43	18.06	1.85			0.26	18157	5399	0.93	R 167R97	4
89	37	15.57	2.1			0.30	15837	4709	1.07	RF167R97	4
96	35	14.52	2.3			0.33	14065	4182	1.20		
110	30	12.69	2.6	R 17	4						
117	28	11.89	2.8	RF17	4	0.29	16193	4815	0.75		
132	25	10.50	2.9			0.32	14545	4325	0.84		
149	22	9.31	3.0			0.38	12339	3669	0.99		
176	19	7.91	3.1			0.43	10856	3228	1.13		
184	18	7.55	3.3			0.49	9528	2833	1.28		
197	17	7.04	3.4			0.54	8593	2555	1.42	R 147R77	4
226	15	6.15	3.5			0.63	7436	2211	1.64	RF147R77	4
241	14	5.76	3.6			0.71	6561	1951	1.86		
273	12	5.09	3.9			0.82	5734	1705	2.1		
308	11	4.51	4.2			0.90	5166	1536	2.4		
363	9	3.83	4.6			1.05	4470	1329	2.7		
						1.19	3921	1166	3.1		
164	21	5.18	3.3	RX 67	6						
188	19	4.53	4.2	RXF67	6	0.52	8939	2658	0.84		
198	18	4.30	4.3			0.56	8354	2484	0.9		
225	15	3.77	5.3			0.58	8112	2412	0.93		
						0.67	6972	2073	1.08		
229	15	6.07	2.7			0.76	6185	1839	1.22	R 137R77	4
268	13	5.18	5.5			0.87	5374	1598	1.40	RF137R77	4
307	12	4.53	6.8			0.99	4698	1397	1.60		
323	11	4.30	7.0			1.1	4123	1226	1.82		
369	9	3.77	8.7	RX 67	4	1.3	3666	1090	2.1		
434	8	3.20	12	RXF67	4	1.5	3198	951	2.4		
481	7	2.89	14			1.7	2795	831	2.7		
547	6.3	2.54	18			1.0	4675	1390	0.86		
579	6.0	2.40	19			1.1	4090	1216	0.99		
681	5.1	2.04	25			1.2	4016	1194	1.01		
						1.3	3686	1095	1.10		
195	17.7	4.35	3.6	RX 57	6	1.4	3508	1043	1.15	R 107R77	4
224	15.4	3.79	4.2	RXF57	6	1.5	3118	927	1.30	RF107R77	4
239	14.5	3.55	4.5			1.6	2986	888	1.35		
						1.7	2731	812	1.48		
						1.8	2647	787	1.53		
						2.0	2327	692	1.74		
						2.3	2035	605	1.99		



造型参数表
Selection Table

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type						极数 Pole						输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type						极数 Pole					
0.55kW						0.55kW																																																																	
1.5	3151	937	0.89																																																																				
1.7	2771	824	1.02																																																																				
1.9	2479	737	1.14																																																																				
2.2	2122	631	1.33																																																																				
2.5	1883	560	1.50	R	97R57	4																																																																	
2.9	1628	484	1.73	RF	97R57	4																																																																	
3.2	1446	430	1.95																																																																				
3.7	1275	379	2.2																																																																				
4.1	1130	336	2.5																																																																				
4.7	995	296	2.8																																																																				
5.6	837	249	3.4																																																																				
2.6	1766	525	0.83																																																																				
2.9	1587	472	0.92																																																																				
3.1	1527	454	0.95																																																																				
3.5	1345	400	1.08	R	87R57	4																																																																	
3.6	1332	396	1.09	RF	87R57	4																																																																	
3.9	1214	361	1.20																																																																				
4.0	1180	351	1.23																																																																				
4.6	1026	305	1.42																																																																				
5.1	925	275	0.83																																																																				
5.9	794	236	0.97	R	77R37	4																																																																	
6.3	743	221	1.04	RF	77R37	4																																																																	
7.8	599	178	1.29																																																																				
2.6	1893	256.89	1.50	R	97	8																																																																	
2.8	1775	240.83	1.59	RF	97	8																																																																	



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
0.55kW											
35	139	39.25	0.88			320	16	4.35	4.0		
38	131	36.79	0.94			367	14	3.79	4.6		
43	115	32.47	1.06			392	13	3.55	4.9		
48	102	28.78	1.20			443	12	3.14	5.3		
57	87	24.47	1.41			478	11	2.91	5.8	RX 57	4
62	79	22.32	1.54			527	10	2.64	6.6	RXF57	4
72	69	19.35	1.78			586	8.8	2.37	7.4		
77	64	18.08	1.90			681	7.6	2.04	8.6		
89	56	15.63	2.2			724	7.1	1.92	9.1		
105	47	13.28	2.6	R 27	4	842	6.1	1.65	11		
117	42	11.86	2.9	RF27	4	939	5.8	1.48	12		
137	36	10.13	3.2			1069	4.8	1.30	12		
148	33	9.41	3.4								
170	29	8.16	3.8			426	12	3.26	1.24		
182	27	7.63	3.9			456	11	3.05	1.33		
211	23	6.59	4.3			527	10	2.64	1.53	RX 37	4
248	20	5.60	4.7			621	8.3	2.24	1.81	RXF37	4
278	18	5.00	5.0			695	7.4	2.00	2.03		
326	15	4.27	5.4			813	6.3	1.71	2.37		
348	14	4.00	5.6			869	5.9	1.60	2.53		
412	12	3.37	6.2								
0.75kW											
77	64	18.06	1.25			0.30	21596	4709	0.8		
89	55	15.57	1.44			0.33	19179	4182	0.88		
96	52	14.52	1.55			0.52	12185	2657	1.39	R 167R97	4
110	45	12.69	1.77			0.60	10699	2333	1.58	RF167R97	4
117	42	11.89	1.89			0.67	9562	2085	1.77		
132	37	10.50	1.9			0.95	6677	1456	2.5		
149	33	9.31	2.0	R 17	4						
161	31	8.63	2.1	RF17	4	0.43	14804	3228	0.83		
176	28	7.91	2.2			0.49	12992	2833	0.94		
184	27	7.55	2.2			0.54	11717	2555	1.04		
197	25	7.04	2.3			0.63	10140	2211	1.21		
226	22	6.15	2.4			0.71	8947	1951	1.37	R 147R77	4
241	20	5.76	2.6			0.82	7819	1705	1.56	RF147R77	4
273	18	5.09	2.7			0.90	7044	1536	1.73		
308	16	4.51	2.8			1.0	6095	1329	2.0		
363	14	3.83	3.1			1.2	5347	1166	2.3		
171	30	5.18	2.3			0.67	9507	2073	0.79		
195	26	4.53	2.9	RX 67	6	0.7	8544	1863	0.88		
206	25	4.30	3.0	RXF67	6	0.76	8434	1839	0.89		
235	22	3.77	3.7			0.87	7287	1589	1.03		
268	19	5.18	3.7			0.9	7273	1586	1.03	R 137R77	4
307	17	4.53	4.6			0.99	6407	1397	1.17	RF137R77	4
323	16	4.30	4.7			1.0	6237	1360	1.21		
369	14	3.77	5.9			1.1	5632	1228	1.34		
434	12	3.20	7.9	RX 67	4	1.2	5623	1226	1.34		
481	11	2.89	9.3	RXF67	4	1.3	4999	1090	1.50		
547	9.4	2.54	12			1.5	4361	951	1.72		
579	8.9	2.40	13			1.7	3811	831	1.97		
681	7.6	2.04	17			1.9	3348	730	2.2		
747	6.9	1.86	17								
863	6.0	1.61	18			1.3	5022	1095	0.80		
203	25	4.35	2.5			1.4	4783	1043	0.85		
234	22	3.79	2.9			1.5	4251	927	0.95		
249	21	3.55	3.1	RX 57	6	1.6	4072	888	0.99	R 107R77	4
282	18	3.14	3.3	RXF57	6	1.7	3724	812	1.09	RF107R77	4
304	17	2.91	3.7			1.8	3609	787	1.12		
						3.9	1637	357	2.5		
						4.4	1435	313	2.8		
						2.2	2894	631	0.97		
						2.5	2568	560	1.10		
						2.9	2220	484	1.27		
						3.2	1972	430	1.43	R 97R57	4
						3.7	1738	379	1.62	RF97R57	4
						4.1	1541	336	1.83		
						4.7	1357	296	2.1		
						5.6	1142	249	2.5		



造型参数表
Selection Table

R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole
0.75kW											
3.5	1816	396	0.80			13	516	106.58	0.82		
3.9	1656	361	0.91			14	479	98.99	0.88		
4.0	1610	351	1.04	R 87	4	15	435	89.71	0.97		
4.6	1399	305	1.19	R 87	4	17	390	80.55	1.08		
4.7	1376	300	1.35	RF87	4	20	335	69.23	1.26		
5.2	1224	267	1.70			21	314	64.85	1.35		
5.4	1174	256	2.0			24	277	57.29	1.52	R 57	4
5.9	1078	235	2.4			26	258	53.22	1.64	RF57	4
2.8	2445	245.50	1.65	R 107	8	29	234	48.23	1.81		
3.0	2259	226.11	1.81	RF107	8	32	210	43.30	2.0		
3.4	1995	200.87	2.0			37	181	37.30	2.3		
3.1	2138	215.94	1.32	R 97	8	40	170	35.07	2.5		
3.7	1841	185.97	1.53	RF97	8	46	146	30.18	2.9		
4.0	1674	169.06	1.68			52	131	26.97	3.2		
3.6	1901	256.89	1.49	R 97	6	53	130	26.31	3.3		
3.8	1782	240.83	1.58	RF97	6	56	124	24.99	3.4		
4.2	1598	215.94	1.76			63	108	21.93	3.9		
4.8	1403	289.60	2.0			75	92	18.60	4.6		
5.4	1244	256.89	2.3			20	332	68.54	0.85		
5.8	1167	240.83	2.4	R 97	4	22	311	64.21	0.91		
6.4	1046	215.94	2.7	RF97	4	25	275	56.73	1.03		
7.5	901	185.97	3.1			26	255	52.69	1.10		
8.2	819	169.06	3.4			29	231	47.75	1.22		
4.2	1602	216.54	0.91			32	208	42.87	1.36		
4.4	1522	205.71	0.96	R 87	6	38	179	36.93	1.58	R 47	4
5.0	1345	181.77	1.08	RF87	6	40	168	34.73	1.68	RF47	4
5.9	1149	155.34	1.27			47	145	29.88	1.95		
6.4	1054	142.41	1.38			52	130	26.74	2.2		
5.6	1194	246.54	1.22			53	129	26.70	2.2		
6.4	1049	216.54	1.39			59	114	23.59	2.5		
6.8	996	205.71	1.46			60	113	23.28	2.5		
7.6	880	181.77	1.65			64	106	21.81	2.7		
8.9	752	155.34	1.94			72	93	19.27	3.0		
9.8	690	142.41	2.1	R 87	4	78	87	17.89	3.1		
11	605	124.97	2.4	RF87	4	86	79	16.22	3.3		
12	574	118.43	2.5			29	233	48.08	0.81		
13	502	103.65	2.9			31	217	44.81	0.87		
15	452	93.38	3.2			35	190	39.17	0.99		
8.3	807	166.59	0.96			38	178	36.72	1.06		
9.5	706	145.67	1.09			43	157	32.40	1.20		
10	670	138.39	1.15			48	139	28.73	1.35		
11	588	121.42	1.31			57	118	24.42	1.59	R 37	4
12	574	118.43	2.5			62	110	22.27	1.71	RF37	4
13	502	103.65	2.9			72	96	19.31	1.97		
15	452	93.38	3.2			77	89	18.05	2.1		
8.3	807	166.59	0.96			89	77	15.60	2.4		
9.5	706	145.67	1.09			105	66	13.25	2.7		
10	670	138.39	1.15			117	59	11.83	2.9		
11	588	121.42	1.31			137	50	10.11	3.2		
13	499	102.99	1.55			147	47	9.47	3.4		
15	450	92.97	1.71	R 77	4	48	139	28.78	0.88		
17	396	81.80	1.95	RF77	4	57	119	24.47	1.03		
18	375	77.24	2.1			62	110	22.32	1.11		
21	319	65.77	2.4			72	96	19.35	1.28		
25	273	56.38	2.8			77	89	18.08	1.37		
27	247	50.90	3.1			89	77	15.63	1.58		
31	217	44.78	3.6			105	66	13.28	1.86		
33	205	42.29	3.8			117	59	11.86	2.1	R 27	4
11	625	128.97	0.90			137	50	10.13	2.3	RF27	4
12	552	113.94	1.02			148	47	9.41	2.5		
13	513	105.83	1.10			170	40	8.16	2.7		
14	465	95.91	1.21			182	38	7.63	2.8		
16	417	86.11	1.35	R 67	4	211	33	6.59	3.1		
19	359	74.17	1.57	RF67	4	248	28	5.60	3.4		
20	338	69.75	1.67			278	25	5.00	3.6		
23	297	61.26	1.90								
24	276	56.89	2.0								
27	250	51.56	2.3								
30	224	46.29	2.5								

造型参数表
 Selection Table


输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
0.75kW											
77	89	18.06	0.89			0.53	17744	2657	0.95		
89	77	15.57	1.04			0.60	15580	2333	1.09		
96	72	14.52	1.11			0.67	13924	2085	1.22		
110	63	12.69	1.27			0.75	12535	1877	1.35	R 167R97	4
117	59	11.89	1.36			0.84	11153	1670	1.52	RF167R97	4
132	52	10.50	1.41			0.96	9723	1456	1.74		
149	46	9.31	1.47	R 17	4	1.1	8655	1296	2.0		
176	39	7.91	1.48	RF17	4	1.2	7593	1137	2.2		
184	37	7.55	1.57								
197	35	7.04	1.67			0.63	14765	2211	0.83		
226	30	6.15	1.73			0.72	13029	1951	0.94		
241	28	5.76	1.75			0.82	11386	1705	1.07		
273	25	5.09	1.90			0.91	10258	1536	1.19		
308	22	4.51	2.0			1.1	8875	1329	1.38	R 147R77	4
363	19	3.83	2.2			1.2	7787	1166	1.57	RF147R77	4
201	35	4.53	2.2			1.4	6872	1029	1.78		
212	33	4.30	2.3	RX 67	6	1.6	5937	889	2.1		
241	29	3.77	2.8	RXF67	6	1.8	5236	784	2.3		
284	25	3.20	3.8			2.0	4641	695	2.6		
268	26	5.18	2.7			1.0	9082	1360	0.83		
307	23	4.53	3.4			1.1	8201	1228	0.92		
323	22	4.30	3.5			1.2	8187	1226	0.92		
369	19	3.77	4.3	RX 67	4	1.3	7279	1090	1.03		
434	16	3.20	5.8	RXF67	4	1.4	6812	1020	1.10		
481	15	2.89	6.8			1.5	6351	951	1.18	R 137R77	4
547	13	2.54	8.6			1.6	5803	869	1.30	RF137R77	4
579	12	2.40	9.5			1.7	5550	831	1.36		
681	10	2.04	12			1.9	4875	730	1.54		
747	9	1.86	13			2.2	4201	629	1.79		
863	8	1.61	13			2.6	3666	549	2.1		
240	29	3.79	2.2			2.9	3272	490	2.3		
256	27	3.55	2.4								
290	24	3.14	2.5	RX 57	6	2.0	4621	692	0.87		
313	22	2.91	2.8	RXF57	6	2.3	3994	598	1.01		
345	20	2.64	3.2			2.6	3539	530	1.14		
320	22	4.35	2.9			2.9	3199	479	1.26	R 107R77	4
367	19	3.79	3.4			3.4	2711	406	1.49	RF107R77	4
392	18	3.55	3.6			3.9	2384	357	1.70		
443	16	3.14	3.9			4.5	2090	313	1.93		
478	15	2.91	4.3	RX 57	4	5.1	1850	277	2.2		
527	13	2.64	4.9	RXF57	4	5.7	1636	245	2.5		
586	12	2.37	5.4								
681	11	2.04	6.3			3.3	2872	430	0.98		
724	10	1.92	6.7			3.7	2531	379	1.11		
842	9	1.65	7.8			4.2	2244	336	1.26	R 97R57	4
939	8	1.48	8.6			4.7	1977	296	1.43	RF97R57	4
1069	7	1.30	9.0			5.6	1663	249	1.70		
456	15	3.05	0.97			6.0	1563	234	1.80		
527	13	2.64	1.13			6.7	1396	209	2.0		
621	11	2.24	1.33	RX 37	4						
695	10	2.00	1.49	RXF37	4	5.2	1783	267	0.82		
813	9	1.71	1.74			5.5	1710	256	0.85		
869	8	1.60	1.86			6.0	1569	235	0.93	R 87R57	4
						6.1	1543	231	0.94	RF87R57	4
						6.7	1389	208	1.05		
						7.2	1302	195	1.12		
						2.8	3586	245.50	1.13		
						3.0	3283	226.11	1.23	R 107	8
						3.4	2901	200.87	1.39	RF107	8
						4.0	2461	167.29	1.64		

R



造型参数表
Selection Table

R

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f _B						机型号 Type					
输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f _B						机型号 Type					
1.1kW																								1.1kW					
3.5	2788	256.89	1.02			R	97		6			20	488	69.23	0.87														
3.8	2613	240.83	1.08			RF	97		6			22	457	64.85	0.92														
4.2	2343	215.94	1.20									24	404	57.29	1.05														
4.9	2018	185.97	1.39									26	375	53.22	1.13														
5.4	1812	256.89	1.56									29	340	48.23	1.24														
5.8	1699	240.83	1.66									32	305	43.30	1.39														
6.5	1523	215.94	1.85									38	263	37.30	1.61	R	57											4	
7.5	1312	185.97	2.1			R	97		4			40	247	35.07	1.71	RF	57										4		
8.3	1192	169.06	2.4			RF	97		4			46	213	30.18	1.99														
9.3	1064	150.78	2.7									52	190	26.97	2.2														
11	894	126.75	3.2									53	186	26.31	2.3														
12	822	116.48	3.4									56	176	24.99	2.4														
6.5	1527	216.54	0.95									64	155	21.93	2.7														
6.8	1451	205.71	1.00									75	131	18.60	3.2														
7.7	1282	181.77	1.14									83	118	16.79	3.6														
9.0	1096	155.34	1.33									29	337	47.75	0.84														
9.8	1004	142.41	1.45									33	302	42.87	0.93														
11	881	124.97	1.65									38	260	36.93	1.08														
12	835	118.43	1.74			R	87		4			40	245	34.73	1.15														
14	731	103.65	1.99			RF	87		4			47	211	29.88	1.34														
15	659	93.38	2.2									52	188	26.70	1.50														
17	578	81.92	2.5									59	166	23.59	1.69														
19	510	72.37	2.9									60	164	23.28	1.72														
22	448	63.50	3.3									64	154	21.81	1.83	R	47									4			
23	424	60.18	3.4									73	136	19.27	2.0	RF	47									4			
27	372	52.67	3.9									78	126	17.89	2.2														
12	856	121.42	0.90									86	114	16.22	2.3														
14	726	102.99	1.06									96	103	14.56	2.4														
15	656	92.97	1.18									112	88	12.54	2.7														
17	577	81.80	1.34									119	83	11.79	2.8														
18	545	77.24	1.41									138	72	10.15	3.0														
21	464	65.77	1.66			R	77		4			154	64	9.07	3.2														
25	398	56.38	1.94			RF	77		4			43	229	32.40	0.82														
28	359	50.90	2.1									49	203	28.73	0.93														
31	316	44.78	2.4									57	172	24.42	1.09														
33	298	42.29	2.6									73	139	19.31	1.35														
39	254	36.01	3.0									78	130	18.05	1.45														
43	231	32.72	3.3									90	112	15.60	1.67														
16	607	86.11	0.93									106	95	13.25	1.87														
19	523	74.17	1.08									118	85	11.83	2.0	R	37									4			
20	492	69.75	1.15									138	73	10.11	2.2	RF	37									4			
23	432	61.26	1.31									148	68	9.47	2.3														
25	401	56.89	1.41									176	57	7.97	2.6														
27	364	51.56	1.55									210	48	6.67	2.8														
30	326	46.29	1.73			R	67		4			247	41	5.67	3.3														
35	281	39.88	1.9			RF	67		4			277	36	5.06	3.5														
37	265	37.50	2.0									72	139	19.35	0.88														
43	228	32.27	2.2									77	130	18.08	0.94														
49	203	28.83	2.4									90	113	15.63	1.09														
50	201	28.13	2.5									105	96	13.28	1.25														
52	192	26.72	2.6									118	85	11.86	1.42														
60	169	23.44	3.1									138	73	10.13	1.57														
70	143	19.89	3.9									172	59	8.16	1.86	R	27									4			
												183	55	7.63	1.92	RF	27									4			
												212	47	6.59	2.1														
												250	40	5.60	2.3														
												280	36	5.00	2.5														
												328	31	4.27	2.7														
												350	29	4.00	2.8														
												415	24	3.37	3.1														

造型参数表
 Selection Table


输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _b	Type	p	r/min	Nm	i	f _b	Type	p
1.1kW						1.5kW					
249	41	5.63	2.5	RX 77	4	1.3	10038	1090	0.75		
262	39	5.35	2.5	RXF77	4	1.4	9393	1020	0.80		
296	35	4.73	3.3			1.5	8758	951	0.86		
						1.6	8003	869	0.94		
201	51	4.53	1.50	RX 67	6	1.7	7653	831	0.98		
212	49	4.30	1.55	RXF67	6	1.9	6723	730	1.12		
241	43	3.77	1.92			2.0	6299	684	1.19	R 137R77	4
						2.2	5792	629	1.30	RF137R77	4
309	33	4.53	2.3			2.4	5479	595	1.37		
326	32	4.30	2.4			2.6	5056	549	1.49		
371	28	3.77	2.9			2.9	4512	490	1.67		
438	24	3.20	4.0			3.3	3941	428	1.91		
484	21	2.89	4.7	RX 67	4	3.7	3444	374	2.2		
551	19	2.54	5.9	RXF67	4	4.4	2919	317	2.6		
583	18	2.40	6.6								
686	15	2.04	8.4			2.6	4827	530	0.84		
753	14	1.86	8.7			2.7	4644	510	0.87		
870	12	1.61	9.1			2.9	4362	479	0.93		
1000	10	1.40	9.5			3.0	4216	463	0.96	R 107R77	4
240	43	3.79	1.5			3.4	3697	406	1.09	RF107R77	4
256	40	3.55	1.6	RX 57	6	3.9	3251	357	1.24		
290	36	3.14	1.7	RXF57	6	4.5	2850	313	1.42		
313	33	2.91	1.9								
345	30	2.64	2.2			4.2	3060	336	0.92		
369	28	3.79	2.3			4.7	2696	296	1.05		
394	26	3.55	2.5			5.6	2268	249	1.24	R 97R57	4
446	23	3.14	2.6			6.0	2131	234	1.32	RF97R57	4
481	21	2.91	2.9			6.7	1903	209	1.48		
530	19	2.64	3.3	RX 57	4						
591	17	2.37	3.7	RXF57	4	3.1	4413	226.11	0.92		
686	15	2.04	4.3			3.5	3920	200.87	1.03	R 107	8
729	14	1.92	4.6			4.1	3265	167.29	1.24	RF107	8
848	12	1.65	5.3			4.4	3045	156.04	1.32		
946	11	1.48	5.9								
1077	10	1.30	6.2			3.7	3593	245.50	1.12		
700	15	2.00	1.02	RX 37	4	4.1	3309	226.11	1.22		
819	13	1.71	1.19	RXF37	4	4.6	2940	200.87	1.37	R 107	6
875	12	1.60	1.27			5.5	2449	167.29	1.65	RF107	6
						5.8	2304	156.04	1.77		
						6.6	2041	139.47	1.98		
1.5kW											
0.60	21246	2333	0.80			5.4	2417	256.89	1.14		
0.67	18987	2085	0.89			5.8	2316	240.83	1.22		
0.75	17093	1877	0.99			6.5	2077	215.94	1.36		
0.84	15208	1670	1.11	R 167R97	4	7.5	1789	185.97	1.58		
0.96	13259	1456	1.28	RF167R97	4	8.3	1626	169.06	1.73	R 97	4
1.1	11802	1296	1.43			9.3	1450	150.78	1.94	RF97	4
1.2	10354	1137	1.63			11	1219	126.75	2.3		
1.4	9213	1012	1.84			12	1120	116.48	2.5		
						14	995	103.44	2.8		
						15	889	92.47	3.2		
3.2	3934	432	3.1	R 147R87	4						
3.8	3388	373	3.6	RF147R87	4	7.7	1748	181.77	0.83		
0.82	15527	1705	0.8			9.0	1494	155.34	0.98		
0.91	13988	1536	0.87			9.8	1370	142.41	1.06		
1.1	12103	1329	1.01			11	1202	124.97	1.21		
1.2	10618	1166	1.15	R 147R77	4	12	1139	118.43	1.28		
1.4	9371	1029	1.30	RF147R77	4	14	997	103.65	1.46		
1.6	8096	889	1.51	RF147R77	4	15	898	93.38	1.62	R 87	4
1.8	7140	784	1.71			17	788	81.92	1.85	RF87	4
2.0	6329	695	1.93			19	696	72.37	2.1		
2.3	5528	607	2.2			22	611	63.50	2.4		
2.6	4981	547	2.5			23	579	60.18	2.5		
						27	507	52.67	2.9		
						30	456	47.45	3.2		
						34	400	41.63	3.6		
						38	353	36.73	4.1		



造型参数表
Selection Table

R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole
1.5kW											
15	894	92.97	0.86			73	186	19.31	1.01		
17	787	81.80	0.98			78	174	18.05	1.08		
18	743	77.24	1.04			90	150	15.60	1.25		
21	633	65.77	1.22			106	127	13.25	1.40		
25	542	56.38	1.42			118	114	11.83	1.51		
28	490	50.90	1.57	R 77	4	138	97	10.11	1.64		
31	431	44.78	1.79	RF77	4	148	91	9.47	1.72	R 37	4
33	407	42.29	1.90			176	77	7.97	1.91	RF37	4
39	346	36.01	2.2			210	64	6.67	2.1		
43	315	32.72	2.4			247	55	5.67	2.4		
49	273	28.35	2.8			277	49	5.06	2.6		
57	237	24.67	3.1			324	42	4.32	2.9		
60	225	23.37	3.4			346	39	4.05	2.9		
65	206	21.43	3.7			411	33	3.41	3.2		
74	181	18.80	4.1			90	150	15.63	0.81		
23	589	61.26	0.96			105	128	13.28	0.96		
25	547	56.89	1.03			118	114	11.86	1.06		
27	496	51.56	1.14			138	97	10.13	1.18		
30	445	46.29	1.27			172	78	8.16	1.39		
35	384	39.88	1.47			183	73	7.63	1.43	R 27	4
37	361	37.50	1.56	R 67	4	212	63	6.59	1.57	RF27	4
43	310	32.27	1.82	RF67	4	250	54	5.60	1.73		
49	277	28.83	2.0			280	48	5.00	1.86		
50	276	28.13	2.0			328	41	4.27	1.99		
52	262	26.72	2.1			350	38	4.00	2.1		
60	230	23.44	2.4			415	32	3.37	2.3		
70	195	19.89	2.9			249	54	5.63	1.91		
78	176	17.95	3.2			262	51	5.35	1.88		
26	523	53.22	0.8			296	45	4.73	2.5		
29	474	48.23	0.9			347	39	4.04	3.5	RX 77	4
32	425	43.30	1.0			378	36	3.70	4.0	RXF77	4
38	366	37.30	1.15			431	31	3.25	5.5		
40	344	35.07	1.23			455	30	3.08	6.1		
46	296	30.18	1.43			519	26	2.70	7.8		
52	265	26.97	1.60	R 57	4	576	23	2.43	8.6		
53	258	26.31	1.64	RF57	4	309	44	4.53	1.77		
56	245	24.99	1.72			326	41	4.30	1.82		
64	215	21.93	1.96			371	36	3.77	2.3		
75	183	18.60	2.3			438	31	3.20	3.1		
83	165	16.79	2.6			484	28	2.89	3.6	RX 67	4
95	145	14.77	2.8			551	24	2.54	4.5	RXF67	4
100	137	13.95	2.9			583	23	2.40	5.0		
118	117	11.88	3.3			686	20	2.04	6.4		
38	355	36.93	0.8			753	18	1.86	6.6		
40	334	34.73	0.84			870	15	1.61	6.9		
47	287	29.88	0.98			1000	13	1.40	7.3		
52	257	26.70	1.1			369	36	3.79	1.78		
59	227	23.59	1.2			394	34	3.55	1.90		
60	224	23.28	1.26			446	30	3.14	2.0		
64	210	21.81	1.34			481	28	2.91	2.3		
73	185	19.27	1.50			530	25	2.64	2.6		
78	172	17.89	1.58			591	23	2.37	2.8	RX 57	4
86	156	16.22	1.66			686	20	2.04	3.3	RF57	4
96	140	14.56	1.8			729	18	1.92	3.5		
112	121	12.54	1.9	R 47	4	848	16	1.65	4.1		
119	113	11.79	2.0	RF47	4	946	14	1.48	4.5		
138	98	10.15	2.1			1077	13	1.30	4.7		
154	87	9.07	2.2								
175	77	8.01	2.3								
180	75	7.76	2.4								
201	67	6.96	2.5								
233	58	6.00	2.5								
248	54	5.64	2.7								
289	47	4.85	3.0								
323	42	4.34	3.3								
366	37	3.83	3.7								

塑型参数表
 Selection Table


输出转速 Output speed r/min						输出转速 Output speed r/min					
输出扭矩 Output torque Nm						输出扭矩 Output torque Nm					
传动比 Ratio i						传动比 Ratio i					
使用系数 Service factor f _B	机型号 Type	极数 Pole p	使用系数 Service factor f _B	机型号 Type	极数 Pole p	使用系数 Service factor f _B	机型号 Type	极数 Pole p	使用系数 Service factor f _B	机型号 Type	极数 Pole p
2.2kW						2.2kW					
0.85	21991	1670	0.8			5.8	3414	245.50	1.18		
0.98	19173	1456	0.88			6.3	3145	226.11	1.29		
1.1	17066	1296	1.0			7.1	2744	200.87	1.45		
1.2	14972	1137	1.1	R 167R97	4	8.5	2327	167.29	1.74	R 107	4
1.4	13326	1012	1.27	RF167R97	4	9.1	2170	156.04	1.86	RF107	4
1.6	11483	872	1.47			10	1940	139.47	2.1		
1.8	10140	770	1.67			11	1746	125.55	2.3		
2.1	8744	664	1.9			12	1581	113.70	2.6		
2.6	7111	540	1.72			14	1402	100.82	2.9		
3.1	6084	462	2.0	R 147R87	4	16	1286	91.16	3.2		
3.3	5689	432	2.1	RF147R87	4						
3.8	4912	373	2.5			6.6	3003	215.94	0.94		
4.3	4346	330	2.8			7.6	2586	185.97	1.09		
1.2	15354	1166	0.80			8.4	2351	169.06	1.20		
1.4	13550	1029	0.90			9.4	2097	150.78	1.34		
1.6	11707	889	1.04			11	1763	126.75	1.60		
1.8	10324	784	1.18	R 147R77	4	12	1620	116.48	1.74	R 97	4
2.0	9152	695	1.34	RF147R77	4	14	1439	103.44	1.96	RF97	4
2.3	7993	607	1.53			15	1286	92.48	2.2		
2.6	7203	547	1.70			17	1156	83.15	2.4		
3.0	6321	480	1.93			20	1004	72.17	2.8		
1.9	9721	730	0.77			22	906	65.12	3.1		
2.1	9108	684	0.83			24	832	59.84	3.4		
2.3	8376	629	0.90			27	739	53.14	3.8		
2.4	7923	595	0.95			30	661	47.51	4.3		
2.6	7311	549	1.03	R 137R77	4						
2.9	6525	490	1.15	RF137R77	4	11	1738	124.97	0.84		
3.3	5699	428	1.32			12	1647	118.43	0.88		
3.8	4980	374	1.51			14	1442	103.65	1.01		
4.5	4221	317	1.78			15	1299	93.38	1.12		
5.0	3808	286	1.97			17	1139	81.92	1.28		
5.6	3377	250	2.2			20	1007	72.37	1.45		
6.4	2958	219	2.5			22	883	63.50	1.65		
3.9	4822	357	0.84			24	837	60.18	1.74	R 87	4
4.4	4336	321	0.93			27	733	52.67	1.99	RF87	4
4.5	4228	313	0.96	R 107R77	4	30	660	47.45	2.2		
5.1	3741	277	1.08	RF107R77	4	34	579	41.63	2.5		
5.5	3458	256	1.17			39	511	36.73	2.9		
6.7	2809	208	1.44			41	478	34.34	3.0		
6.0	3125	234	0.90	R 97R57	4	44	453	32.57	3.2		
6.7	2791	209	1.01	RF97R57	4	45	434	31.22	3.4		
3.2	6212	223.34	1.21			51	387	27.81	3.8		
3.8	5234	188.16	1.43			61	325	23.40	4.5		
4.1	4851	174.4	1.55			66	299	21.51	4.7		
4.5	4348	156.31	1.73	R 137	8						
5.0	3925	141.12	1.92	RF137	8	22	915	65.77	0.8		
5.5	3565	128.18	2.1			25	784	56.38	1.0		
6.2	3163	113.72	2.4			28	708	50.90	1.1		
6.9	2871	103.2	2.6			32	623	44.78	1.2		
4.7	4220	200.87	0.96			34	588	42.29	1.31		
5.6	3515	167.29	1.15	R 107	6	39	501	36.01	1.54		
6.0	3278	156.04	1.23	RF107	6	43	455	32.72	1.69	R 77	4
6.7	2930	139.47	1.38			50	394	28.35	1.95	RF77	4

R



造型参数表
Selection Table

R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole
2.2kW											
36	555	39.88	0.98			300	69	4.73	1.69		
38	522	37.50	1.03			351	59	4.04	2.3		
44	449	32.27	1.13			384	54	3.70	2.7		
49	401	28.83	1.22			437	47	3.25	3.6		
61	326	23.44	1.61			461	45	3.08	4.1	RX 77	4
71	277	19.89	2.0	R 67	4	526	39	2.70	5.2	RXF77	4
79	250	17.95	2.2	RF67	4	584	35	2.43	5.7		
90	220	15.79	2.4			667	31	2.13	6.1		
95	207	14.91	2.5			755	27	1.88	6.4		
112	177	12.70	2.8			850	24	1.67	6.7		
123	160	11.54	2.9			1000	21	1.42	7.1		
142	139	10.00	3.2								
163	121	8.70	3.3			377	55	3.77	1.50		
182	108	7.79	3.4			444	46	3.20	2.0		
38	519	37.30	0.82			491	42	2.89	2.4		
40	488	35.07	0.87			559	37	2.54	3.0	RX 67	4
47	420	30.18	1.01			592	35	2.40	3.3	RXF67	4
53	375	26.97	1.13			696	30	2.04	4.3		
65	305	21.93	1.39			763	27	1.86	4.4		
76	259	18.60	1.64			882	23	1.61	4.6		
85	234	16.79	1.81	R 57	4	1014	20	1.40	4.8		
96	205	14.77	1.99	RF57	4						
102	194	13.95	2.1			452	46	3.14	1.34		
120	165	11.88	2.3			538	38	2.64	1.69		
132	150	10.79	2.4			599	34	2.37	1.89		
152	130	9.35	2.7			696	30	2.04	2.2	RX 57	4
157	126	9.06	2.8			740	28	1.92	2.3	RXF57	4
178	111	7.97	3.0			861	24	1.65	2.7		
74	268	19.27	1.03			959	21	1.48	3.0		
88	226	16.22	1.15			1092	19	1.30	3.1		
98	203	14.56	1.23								
113	174	12.54	1.35								
120	164	11.79	1.40								
140	141	10.15	1.53								
157	126	9.07	1.64	R 47	4						
177	111	8.01	1.73	RF47	4	1.2	20417	1137	0.83		
183	108	7.76	1.42			1.4	18172	1012	0.93		
204	97	6.96	1.54			1.6	15658	872	1.08	R 167R97	4
237	83	6.00	1.76			1.8	13827	770	1.22	RF167R97	4
252	78	5.64	1.86			2.1	11923	664	1.42		
293	67	4.85	2.1			2.8	9158	510	1.85		
327	60	4.34	2.3								
371	53	3.83	2.5			2.6	9697	540	1.26		
91	217	15.60	0.87			3.1	8296	462	1.47		
107	184	13.25	0.97			3.3	7757	432	1.58	R 147R87	4
120	165	11.83	1.05			3.8	6698	373	1.82	RF147R87	4
140	141	10.11	1.14			4.3	5926	330	2.1		
150	132	9.47	1.19			5.0	5082	283	2.4		
178	111	7.97	1.32	R 37	4						
213	93	6.67	1.46	RF37	4	1.6	15963	889	0.8		
250	79	5.67	1.69			1.8	14078	784	0.87		
281	70	5.06	1.80			2.0	12480	695	0.98	R 147R77	4
329	60	4.32	2.0			2.3	10900	607	1.12	RF147R77	4
351	56	4.05	2.0			2.6	9822	547	1.24		
416	47	3.41	2.2								
140	141	10.13	0.81			2.7	9388	517	0.80		
215	92	6.59	1.09			2.9	8898	490	0.85		
254	78	5.60	1.19			3.1	8226	453	0.91		
284	70	5.00	1.28	R 27	4	3.3	7772	428	0.97		
333	59	4.27	1.38	RF27	4	3.8	6791	374	1.11	R 137R77	4
355	56	4.00	1.44			4.5	5756	317	1.31	RF137R77	4
421	47	3.37	1.58			5.0	5193	286	1.45		
140	141	10.13	0.81			5.7	4540	250	1.66		
215	92	6.59	1.09			6.5	3977	219	1.89		
254	78	5.60	1.19								
284	70	5.00	1.28			5.6	4798	253	0.84		
333	59	4.27	1.38			5.8	4647	245	0.87	R 107R77	4
355	56	4.00	1.44			6.8	3945	208	1.02	RF107R77	4
421	47	3.37	1.58			7.8	3433	181	1.18		

造型参数表
 Selection Table


输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
3.0kW											
3.2	8472	223.34	0.89			32	849	44.78	0.91		
3.8	7137	188.16	1.05			34	802	42.29	0.96		
4.1	6615	174.40	1.14			39	683	36.01	1.13		
4.5	5929	156.31	1.27	R 137	8	43	621	32.72	1.24		
5.0	5353	141.12	1.40	RF137	8	50	538	28.35	1.43		
5.5	4862	128.18	1.55			58	468	24.67	1.57		
6.2	4314	113.72	1.74			61	443	23.37	1.74		
6.9	3914	103.20	1.92			66	406	21.43	1.90	R 77	4
8.0	3364	88.70	2.20			76	357	18.80	2.1	RF77	4
						80	338	17.82	2.2		
4.3	6245	222.60	1.20			91	296	15.60	2.4		
5.1	5287	188.45	1.42			101	266	14.05	2.5		
5.5	4892	174.40	1.54			115	234	12.33	2.8		
6.1	4385	156.31	1.71	R 137	6	131	206	10.88	3.0		
6.8	3959	141.12	1.90	RF137	6	147	183	9.64	3.2		
7.5	3596	128.18	2.10			169	160	8.42	3.7		
8.4	3190	113.72	2.40			187	144	7.59	4.0		
9.3	2895	103.20	2.60			213	126	6.66	4.3		
6.2	4377	156.04	0.92	R 107	6	61	445	23.44	1.18		
6.9	3913	139.47	1.03	RF107	6	71	377	19.89	1.50		
7.6	3522	125.55	1.15			79	340	17.95	1.63		
6.3	4288	226.11	0.94			90	299	15.79	1.76	R 67	4
7.1	3810	200.87	1.06			95	283	14.91	1.8	RF67	4
8.5	3172	167.29	1.27			112	241	12.70	2.0		
9.1	2959	156.04	1.37			123	219	11.54	2.1		
10	2645	139.47	1.53			142	190	10.00	2.3		
11	2381	125.55	1.70	R 107	4	53	511	26.97	0.8		
12	2156	113.70	1.87	RF107	4	65	416	21.93	1.02		
14	1912	100.82	2.1			76	353	18.60	1.20		
16	1729	91.16	2.3			85	318	16.79	1.33		
18	1465	77.26	2.8			96	280	14.77	1.46		
20	1366	72.00	3.0			102	265	13.95	1.53		
						120	225	11.88	1.69		
9.4	2860	150.78	0.99			132	205	10.79	1.79	R 57	4
11	2404	126.75	1.17			152	177	9.35	2.0	RF57	4
12	2209	116.48	1.28			157	172	9.06	2.1		
14	1962	103.44	1.44			178	151	7.97	2.2		
15	1754	92.48	1.61			189	143	7.53	2.3		
17	1577	83.15	1.79	R 97	4	222	122	6.41	2.6		
20	1369	72.17	2.1	RF97	4	244	110	5.82	2.7		
22	1235	65.12	2.3			281	96	5.05	3.0		
24	1135	59.84	2.5			323	83	4.39	3.2		
27	1008	53.14	2.8			88	308	16.22	0.84		
30	901	47.51	3.1			98	276	14.56	0.90		
33	810	42.72	3.5			113	238	12.54	0.99		
38	703	37.08	4.0			120	224	11.79	1.03		
43	630	33.20	4.3			140	192	10.15	1.12		
15	1771	93.38	0.82			157	172	9.07	1.20		
17	1554	81.92	0.94			177	152	8.01	1.27	R 47	4
20	1373	72.37	1.06			183	147	7.76	1.04	RF47	4
22	1204	63.50	1.21			204	132	6.96	1.13		
24	1141	60.18	1.28			237	114	6.00	1.29		
27	999	52.67	1.46			252	107	5.64	1.36		
30	900	47.45	1.62			293	92	4.85	1.53		
34	790	41.63	1.85	R 87	4	327	82	4.34	1.67		
39	697	36.73	2.1	RF87	4	371	73	3.83	1.86		
41	651	34.34	2.2			140	192	10.11	0.83		
44	618	32.57	2.4			150	180	9.47	0.87		
45	592	31.22	2.5			178	151	7.97	0.97		
51	528	27.84	2.8			213	126	6.67	1.07	R 37	4
53	527	27.81	2.8			250	108	5.67	1.24	RF37	4
61	444	23.40	3.3			281	96	5.06	1.32		
66	408	21.51	3.5			329	82	4.32	1.45		
74	362	19.10	3.6			351	77	4.05	1.49		
83	324	17.08	4.0			416	65	3.41	1.63		
93	291	15.35	4.3								

R



造型参数表
Selection Table

R

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type		极数 Pole		输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type		极数 Pole	
3.0kW						4.0kW						3.0kW						4.0kW						R		4		4.0kW						4.0kW						R		4													
254 106 5.60 0.88						254 8877 376 0.85						254 8830 374 0.85						254 8004 339 0.94						R 27		4		254 7484 317 1.00						254 7012 297 1.07						R 137R77		4													
284 95 5.00 0.94						284 6752 286 1.11						284 5902 250 1.27						284 5171 219 1.45						RF27		4		284 5171 219 1.45						284 5171 219 1.45						RF137R77		4													
333 81 4.27 1.01						333 5.8 4509 191 0.90						333 4.8 4273 181 0.95						333 4.8 3943 167 1.03						R 127		8		333 5.8 4509 191 0.90						333 5.8 4509 191 0.90						R 107R77		4													
355 76 4.00 1.05						355 5.8 3943 167 1.03						355 5.8 3943 167 1.03						355 5.8 3943 167 1.03						RF27		4		355 5.8 3943 167 1.03						355 5.8 3943 167 1.03						RF137R77		4													
421 64 3.37 1.2						421 5.8 3943 167 1.03						421 5.8 3943 167 1.03						421 5.8 3943 167 1.03						R 127		8		421 5.8 3943 167 1.03						421 5.8 3943 167 1.03						R 107R77		4													
4.0kW						4.0kW						4.0kW						4.0kW						R		4		4.0kW						4.0kW						R		4													
220 127 6.44 1.42						220 7.5 4509 191 0.90						220 8.0 4273 181 0.95						220 8.6 3943 167 1.03						RX 87		4		220 7.5 4509 191 0.90						220 7.5 4509 191 0.90						R 107R77		4													
256 110 5.55 1.92						256 8.6 3943 167 1.03						256 8.6 3943 167 1.03						256 8.6 3943 167 1.03						RXF87		4		256 8.6 3943 167 1.03						256 8.6 3943 167 1.03						RF107R77		4													
281 100 5.05 2.3						281 4.4 8152 163.46 1.50						281 4.9 7324 146.85 1.67						281 6.0 5946 119.24 2.0						RXF87		4		281 4.4 8152 163.46 1.50						281 4.4 8152 163.46 1.50						R 147		8													
316 89 4.50 3.1						316 6.5 5487 110.03 2.2						316 7.0 5147 103.20 1.46						316 5.6 6393 128.18 1.18						RXF77		4		316 5.6 6393 128.18 1.18						316 5.6 6393 128.18 1.18						R 147		8													
376 75 3.78 3.8						376 7.0 5147 103.20 1.46						376 7.5 4794 128.18 1.57						376 8.4 4254 113.72 1.77						RXF77		4		376 7.5 4794 128.18 1.57						376 7.5 4794 128.18 1.57						R 147		8													
300 94 4.73 1.24						300 6.0 5946 119.24 2.0						300 6.5 5487 110.03 2.2						300 6.5 5487 110.03 2.2						RX 77		4		300 6.5 5487 110.03 2.2						300 6.5 5487 110.03 2.2						R 147		8													
351 80 4.04 1.68						351 6.5 5487 110.03 2.2						351 7.0 5147 103.20 1.46						351 7.5 4794 128.18 1.57						RXF77		4		351 7.5 4794 128.18 1.57						351 7.5 4794 128.18 1.57						R 147		8													
384 73 3.70 1.97						384 7.0 5147 103.20 1.46						384 7.5 4794 128.18 1.57						384 8.0 4254 113.72 1.77						RXF77		4		384 7.5 4794 128.18 1.57						384 7.5 4794 128.18 1.57						R 147		8													
437 64 3.25 2.7						437 7.5 5147 103.20 1.46						437 8.0 4794 128.18 1.57						437 8.5 4254 113.72 1.77						RXF77		4		437 7.5 5147 103.20 1.46						437 7.5 5147 103.20 1.46						R 147		8													
461 61 3.08 3.0						461 7.0 5147 103.20 1.46						461 7.5 4794 128.18 1.57						461 8.0 4254 113.72 1.77						RXF77		4		461 7.0 5147 103.20 1.46						461 7.0 5147 103.20 1.46						R 147		8													
4.0kW						4.0kW						4.0kW						4.0kW						R		4																													

塑型参数表
 Selection Table


输出转速	输出扭矩	传动比	使用系数	机型号	极数	输出转速	输出扭矩	传动比	使用系数	机型号	极数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _b	Type	p	r/min	Nm	i	f _b	Type	p
4.0kW						4.0kW					
23	1583	63.5	0.92	R 87 RF87	4	142	253	10.15	0.85	RX 127 RXF127	8
24	1501	60.18	0.97			159	226	9.07	0.86		
27	1313	52.67	1.11			180	200	8.01	0.91		
30	1183	47.45	1.23			207	174	6.96	0.96	R 47	4
35	1038	41.63	1.40			240	150	6.00	0.98	RF47	4
39	916	36.73	1.59			255	141	5.64	1.04		
42	856	34.34	1.70			297	121	4.85	1.17		
44	812	32.57	1.79			332	108	4.34	1.27		
46	779	31.22	1.87			376	96	3.83	1.42		
52	694	27.84	2.1								
53	693	27.81	2.2			109	344	6.47	3.23	RX 127	8
62	584	23.40	2.5			121	310	5.88	3.59	RXF127	8
67	536	21.51	2.7								
75	476	19.10	3.1			147	254	6.47	4.37	RX 127	6
84	426	17.08	3.1							RXF127	6
94	383	15.35	3.3								
108	332	13.33	3.6			259	144	5.55	1.46		
121	297	11.93	3.9			285	131	5.05	1.78	RX 87	4
						320	117	4.50	2.3	RXF87	4
40	898	36.01	0.86			381	98	3.78	2.9		
44	816	32.72	0.94								
51	707	28.35	1.09			356	105	4.04	1.28		
58	615	24.67	1.19			389	96	3.70	1.50		
62	583	23.37	1.32			443	84	3.25	2.0		
67	534	21.43	1.44			468	80	3.08	2.3		
77	469	18.80	1.56			533	70	2.70	2.9		
81	444	17.82	1.65			593	63	2.43	3.2	RX 77	4
92	389	15.60	1.79			676	55	2.13	3.4	RXF77	4
102	350	14.05	1.93			766	49	1.88	3.6		
117	307	12.33	2.1			862	43	1.67	3.7		
132	271	10.88	2.3			1014	37	1.42	3.9		
149	240	9.64	2.5								
171	210	8.42	2.8			450	83	3.20	1.13		
190	189	7.59	3.0			498	75	2.89	1.33		
216	166	6.66	3.3			567	66	2.54	1.68		
245	147	5.88	3.5			600	62	2.40	1.85	RX 67	4
276	130	5.21	3.7			706	53	2.04	2.4	RXF67	4
						774	48	1.86	2.4		
72	496	19.89	1.14			894	42	1.61	2.6		
80	448	17.95	1.24			1029	36	1.40	2.7		
91	394	15.79	1.34								
97	372	14.91	1.39			545	69	2.64	0.95		
113	317	12.70	1.54			608	62	2.37	1.05		
125	288	11.54	1.63			706	53	2.04	1.22	RX 57	4
144	249	10.00	1.77			750	50	1.92	1.30	RXF57	4
166	217	8.70	1.91			873	43	1.65	1.51		
185	194	7.79	1.84			973	38	1.48	1.66		
196	184	7.36	1.90			1108	34	1.30	1.75		
230	156	6.27	2.0								
253	142	5.70	2.1								
292	123	4.93	2.2								
336	107	4.29	2.4								
77	464	18.60	0.91			2.2	21556	664	0.80		
86	419	16.79	1.01			2.5	18764	578	0.90		
97	368	14.77	1.11			2.8	16556	510	1.02		
103	348	13.95	1.16			3.3	14219	438	1.19	R 167R97	4
121	296	11.88	1.29			3.8	12336	380	1.37	RXF167R97	4
133	269	10.79	1.36			4.3	10973	338	1.54		
154	233	9.35	1.49			4.7	9966	307	1.70		
159	226	9.06	1.56			5.1	9155	282	1.85		
181	199	7.97	1.68			3.1	14998	462	0.81		
191	188	7.53	1.75			3.3	14024	432	0.87		
225	160	6.41	1.97			3.9	12109	373	1.01		
247	145	5.82	2.1			4.4	10713	330	1.14	R 147R87	4
285	126	5.05	2.3			5.1	9187	283	1.33	RXF147R87	4
328	109	4.39	2.4			5.8	8116	250	1.51		
						6.7	7012	216	1.74		
						7.5	6201	191	1.97		



造型參數表


 齿型参数表
Selection Table

输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
5.5kW						7.5kW					
116	443	6.22	3.79	RX 157	8	4.4	14408	330	0.85		
				RXF157	8	5.2	12356	283	0.99		
123	420	5.88	2.64	RX 127	8	5.8	10915	250	1.12	R 147R87	4
				RXF127	8	6.8	9431	216	1.30	RF147R87	4
147	350	6.47	3.18	RX 127	6	7.6	8339	191	1.47		
164	315	5.88	3.53	RXF127	6	9.1	7030	161	1.74		
182	283	5.28	3.92								
217	238	6.65	1.82			3.7	18366	196.41	0.92		
257	200	5.60	2.14	RX 107	4	4.5	15036	160.80	1.13	R 167	4
277	186	5.19	3.52	RXF107	4	5.5	12197	130.44	1.39	RF167	4
310	166	4.65	3.93			6.0	11314	120.99	1.50		
247	208	5.82	1.9			6.9	9763	104.41	1.73		
297	173	4.85	2.1			4.9	13775	196.41	1.23		
319	162	4.52	3.5			6.0	11277	160.80	1.50		
356	144	4.04	3.9			7.4	9145	130.44	1.84		
396	130	3.64	4.3	RX 97	4	7.9	8485	120.99	1.99		
436	118	3.30	4.7	RXF97	4	9.2	7323	104.41	2.31	R 167	6
493	104	2.92	5.4			10	6462	92.14	2.6	RF167	6
545	94	2.64	5.9			12	5602	79.88	3.0		
643	80	2.24	7.0			14	4984	71.07	3.4		
735	70	1.96	7.6			15	4487	63.98	3.8		
878	59	1.64	8.1			16	4103	58.51	4.1		
1014	51	1.42	8.4			4.4	15285	163.46	0.80		
320	161	4.50	1.7			4.9	13732	146.85	0.89	R 147	8
381	135	3.78	2.1			6.0	11150	119.24	1.09	RF147	8
414	124	3.48	3.1	RX 87	4	6.6	10289	110.03	1.20		
466	110	3.09	3.4	RXF87	4	5.9	11464	163.46	1.07		
522	99	2.76	3.9			6.5	10299	146.85	1.19		
581	89	2.48	4.3			8.0	8363	119.24	1.45	R 147	6
670	77	2.15	4.7			8.8	7717	110.03	1.59	RF147	6
443	116	3.25	1.47			10	6635	94.60	1.84		
468	110	3.08	1.65			12	5854	83.47	2.1		
533	97	2.70	2.1			7.7	8677	188.16	0.87		
593	87	2.43	2.3	RX 77	4	8.4	8042	174.40	0.94		
676	76	2.13	2.5	RXF77	4	9.3	7208	156.31	1.04		
766	67	1.88	2.6			10	6508	141.12	1.16		
862	60	1.67	2.7			11	5911	128.18	1.27	R 137	4
1014	51	1.42	2.9			13	5244	113.72	1.43	RF137	4
567	91	2.54	1.22			14	4759	103.20	1.58		
600	86	2.40	1.35			16	4090	88.70	1.84		
706	73	2.04	1.73	RX 67	4	18	3731	80.91	2.0		
774	66	1.86	1.78	RXF67	4	20	3389	73.49	2.2		
894	58	1.61	1.86			22	3007	65.20	2.5		
1029	50	1.40	2.0			25	2729	59.17	2.8		
706	73	2.04	0.89			29	2345	50.86	3.2		
750	69	1.92	0.95			16	4204	91.16	0.96		
873	59	1.65	1.10	RX 57	4	19	3563	77.26	1.13		
973	53	1.48	1.21	RXF57	4	20	3320	72.00	1.22		
1108	46	1.30	1.27			23	2989	64.81	1.35		
7.5kW						25	2706	58.69	1.49		
2.9	22268	510	0.80			28	2400	52.05	1.68	R 107	4
3.3	19124	438	0.88			31	2170	47.06	1.86	RF107	4
3.8	16591	380	1.02	R 167R97	4	37	1839	39.88	2.2		
4.3	14758	338	1.15	RF167R97	4	42	1607	34.84	2.5		
4.8	13404	307	1.26			48	1404	30.44	2.9		
5.2	12313	282	1.37			50	1344	29.14	3.0		

R



造型参数表

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type p						输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type p					
7.5kW												7.5kW																																															
24	2760	59.84	1.02									123	572	5.88	2.94									RX	127	6																																	
27	2451	53.14	1.15									136	515	5.28	3.26									RXF	127	6																																	
31	2191	47.51	1.29									167	420	4.29	4.0																																												
34	1970	42.72	1.43																																																								
39	1710	37.08	1.65									R	97			4																																											
44	1531	33.20	1.72									RF	97			4																																											
45	1486	32.22	1.77																																																								
53	1270	27.54	1.94																																																								
54	1238	26.84	1.98																																																								
58	1154	25.03	2.30																																																								
65	1032	22.37	2.48																																																								
72	929	20.14	2.64																																																								
80	841	18.24	2.79																																																								
40	1694	36.73	0.86																																																								
45	1502	32.57	0.97																																																								
52	1284	27.84	1.13																																																								
53	1282	27.81	1.1																																																								
62	1079	23.40	1.35																																																								
68	992	21.51	1.42																																																								
76	881	19.10	1.54																																																								
85	788	17.08	1.66									R	87			4																																											
95	708	15.35	1.78									RF	87			4																																											
110	615	13.33	1.96																																																								
122	550	11.93	2.1																																																								
147	457	9.90	2.4																																																								
158	427	9.25	2.7																																																								
175	384	8.32	2.8																																																								
202	333	7.22	3.0																																																								
226	298	6.47	3.2																																																								
272	247	5.36	3.5																																																								
78	867	18.80	0.85																																																								
82	822	17.82	0.89																																																								
94	719	15.60	0.97																																																								
104	648	14.05	1.04																																																								
118	569	12.33	1.14									R	77			4																																											
134	502	10.88	1.24									RF	77			4																																											
151	445	9.64	1.33																																																								
173	388	8.42	1.53																																																								
192	350	7.59	1.64																																																								
219	307	6.66	1.78																																																								
248	271	5.88	1.87																																																								
280	240	5.21	2.00																																																								
115	586	12.70	0.83																																																								
127	532	11.54	0.88																																																								
146	461	10.00	0.96																																																								
168	401	8.70	0.99																																																								
187	359	7.79	1.02									R	67			4																																											
198	339	7.36	1.03									RF	67			4																																											
233	289	6.27	1.07																																																								
256	263	5.70	1.11																																																								
296	227	4.93	1.20																																																								
289	233	5.05	1.23																																																								
333	202	4.39	1.30																																																								
183	368	7.97	0.91																																																								
194	347	7.53	0.95																																																								
228	296	6.41	1.07									R	57			4																																											

造型参数表
Selection Table

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
11kW											
6.0	16540	160.80	1.02	R 167	6	135	732	10.83	2.7	R 97	4
7.4	13417	130.44	1.26	RF167	6	158	626	9.26	3.0	RF97	4
7.9	12445	120.99	1.36			174	566	8.37	3.4		
9.2	10740	104.41	1.58			206	480	7.09	3.9		
						235	419	6.20	4.2		
7.4	13284	196.41	1.27			68	1455	21.51	0.97		
9.1	10876	160.80	1.56			76	1292	19.10	1.05		
11	8822	130.44	1.91			85	1155	17.08	1.13		
12	8183	120.99	2.07	R 167	4	95	1038	15.35	1.21		
14	7062	104.41	2.4	RF167	4	110	902	13.33	1.33		
16	6232	92.14	2.7			122	807	11.93	1.43	R 87	4
18	5403	79.88	3.1			147	670	9.90	1.66	RF87	4
21	4807	71.07	3.5			158	626	9.25	1.82		
6.5	15105	146.85	0.81			175	563	8.32	1.94		
8.1	12265	119.24	1.0	R 147	6	202	488	7.22	2.1		
8.7	11318	110.03	1.08	RF147	6	226	438	6.47	2.2		
10	9731	94.60	1.26			272	363	5.36	2.4		
12	8586	83.47	1.42			134	736	10.88	0.84		
8.9	11056	163.46	1.11			151	652	9.64	0.91		
10	9932	146.85	1.23			192	513	7.59	1.12	R 77	4
12	8065	119.24	1.52			219	450	6.66	1.21	RF77	4
13	7442	110.03	1.64	R 147	4	248	398	5.88	1.28		
15	6398	94.60	1.91	RF147	4	280	352	5.21	1.36		
17	5645	83.47	2.2			191	539	5.05	3.12	RX 157	6
20	4876	72.09	2.5			209	492	4.68	3.41	RXF157	6
22	4508	66.65	2.7			240	429	4.04	3.92		
24	4129	61.50	3.0			235	437	6.22	3.84	RX 157	4
28	3576	52.87	3.4			281	366	5.19	1.79	RXF157	4
10	9545	141.12	0.80			314	328	4.65	1.99		
11	8669	128.18	0.87			348	296	4.20	2.63	RX 127	4
13	7691	113.72	0.98			339	304	4.29	3.65	RXF127	4
14	6980	103.2	1.08			372	277	3.95	4.01		
16	5999	88.70	1.25			281	281	5.19	1.79		
18	5472	80.91	1.37	R 137	4	314	328	4.65	1.99		
20	4970	73.49	1.51	RF137	4	348	296	4.20	2.63	RX 107	4
22	4410	65.20	1.71			383	269	3.81	2.90	RXF107	4
25	4002	59.17	1.88			432	238	3.38	3.27		
29	3440	50.86	2.2			476	216	3.07	3.60		
33	3002	44.39	2.5			553	186	2.64	4.19		
39	2540	37.65	3.0			323	319	4.52	1.75		
44	2226	32.91	3.4			361	285	4.04	1.96		
23	4383	64.81	0.92			401	257	3.64	2.2		
25	3969	58.69	1.02			442	233	3.30	2.4		
28	3520	52.05	1.15			500	206	2.92	2.7	RX 97	4
31	3183	47.06	1.27			553	186	2.64	3.0	RXF97	4
37	2697	39.88	1.50			652	158	2.24	3.5		
42	2356	34.84	1.72	R 107	4	745	138	1.96	3.9		
48	2059	30.44	1.96	RF107	4	890	116	1.64	4.1		
50	1971	29.14	2.1			1028	110	1.42	4.3		
54	1843	27.25	2.2			420	245	3.48	1.55		
59	1664	24.60	2.4			472	218	3.09	1.75		
65	1511	22.34	2.7			529	195	2.76	1.96		
74	1341	19.82	3.0			589	175	2.48	2.2	RX 87	4
81	1217	17.99	3.3			679	152	2.15	2.4	RXF87	4
34	2889	42.72	0.98			756	136	1.93	2.5		
39	2508	37.08	1.12			913	113	1.60	2.6		
44	2245	33.20	1.21			1050	98	1.39	2.8		
53	1863	27.54	1.35	R 97	4	601	171	2.43	1.18		
58	1693	25.03	1.57	RF97	4	685	150	2.13	1.25	RX 77	4
65	1513	22.37	1.69			777	133	1.88	1.33	RXF77	4
72	1362	20.14	1.80			874	118	1.67	1.38		
80	1234	18.24	1.90			1028	100	1.42	1.46		
90	1094	16.17	2.1								
100	989	14.62	2.2								
118	838	12.39	2.5								



造型参数表
Selection Table

R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole
15kW											
6.1	20783	238	0.81			53	2540	27.54	1.1		
6.5	19560	224	0.87	R 167	4	58	2309	25.03	1.15		
7.0	18163	208	0.93	RF167	4	65	2063	22.37	1.24		
7.5	17028	195	0.99			72	1858	20.14	1.32		
8.3	15369	176	1.10			80	1682	18.24	1.40		
7.4	18201	130.44	0.93			90	1491	16.17	1.51	R 97	4
8.0	16883	120.99	1.00	R 167	6	100	1348	14.62	1.6	RF97	4
9.2	14569	104.41	1.16	RF167	6	118	1143	12.39	1.8		
11	12857	92.14	1.32			135	999	10.83	2.0		
7.4	18115	196.41	0.93			158	854	9.26	2.4		
9.1	14830	160.80	1.14			174	772	8.37	2.5		
11	12030	130.44	1.41			206	654	7.09	2.9		
12	11159	120.99	1.52			235	572	6.20	3.1		
14	9630	104.41	1.76	R 167	4	85	1575	17.08	0.89		
16	8498	92.14	1.99	RF167	4	95	1416	15.35	0.98		
18	7367	79.88	2.3			110	1229	13.33	1.05		
21	6555	71.07	2.6			122	1100	11.93	1.13	R 87	4
23	5901	63.98	2.9			147	913	9.90	1.21	RF87	4
25	5396	58.51	3.1			158	853	9.25	1.33		
8.8	15353	110.03	0.80			175	767	8.32	1.42		
10	13200	94.60	0.93			202	666	7.22	1.51		
12	11647	83.47	1.05	R 147	6	226	597	6.47	1.61		
13	10059	72.09	1.21	RF147	6	272	494	5.36	1.73		
14	9300	66.65	1.31			287	488	5.05	3.44	RX 157	4
8.9	15076	163.46	0.81			315	446	4.68	3.77	RXF157	4
9.9	13544	146.86	0.90			361	388	4.04	3.32		
12	10997	119.24	1.11			372	378	3.95	2.94	RX 127	4
13	10148	110.03	1.20			314	479	5.19	1.36	RXF127	4
15	8725	94.60	1.40	R 147	4	348	429	4.65	1.52		
17	7698	83.47	1.59	RF147	4	383	387	4.20	2.0		
20	6649	72.09	1.84			432	325	3.38	2.4	RX 107	4
22	6147	66.65	1.99			476	295	3.07	2.6	RXF107	4
24	5631	61.50	2.2			553	254	2.64	3.1		
28	4876	52.87	2.5			635	221	2.30	3.5		
31	4303	46.65	2.8			749	188	1.95	3.8		
14	9518	103.2	0.8			854	164	1.71	4.0		
16	8181	88.70	0.92			1014	138	1.44	4.4		
18	7462	80.91	1.01			323	435	4.52	1.3		
20	6778	73.49	1.11			361	388	4.04	1.4		
22	6013	65.20	1.25			401	350	3.64	1.6		
25	5457	59.17	1.38	R 137	4	442	317	3.30	1.8		
29	4691	50.86	1.60	RF137	4	500	281	2.92	2.0	RX 97	4
33	4094	44.39	1.84			553	254	2.64	2.2	RXF97	4
39	3472	37.65	2.2			652	215	2.24	2.6		
44	3035	32.91	2.5			745	188	1.96	2.8		
52	2567	27.83	2.9			890	158	1.64	3.0		
31	4340	47.06	0.9			1028	137	1.42	3.1		
37	3678	39.88	1.10			420	335	3.48	1.14		
42	3213	34.84	1.26			472	297	3.09	1.28		
48	2807	30.44	1.44			529	265	2.76	1.43		
50	2688	29.14	1.50			589	238	2.48	1.60	RX 87	4
54	2513	27.25	1.61	R 107	4	679	207	2.15	1.75	RXF87	4
59	2269	24.60	1.78	RF107	4	756	186	1.93	1.80		
65	2060	22.34	1.96			913	154	1.60	1.92		
74	1828	19.82	2.2			1050	134	1.39	2.0		
81	1659	17.99	2.4								
94	1426	15.46	2.8								
108	1245	13.50	3.2								

塑型参数表
 Selection Table


输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
18.5kW											
9.1	18291	160.80	0.93			110	1516	13.33	0.8		
11	14838	130.44	1.13			122	1357	11.93	0.85		
12	13763	120.99	1.24			147	1126	9.90	0.98		
14	11877	104.41	1.42	R 167	4	158	1052	9.25	1.08	R 87	4
16	10481	92.14	1.61	RF167	4	175	946	8.32	1.15	RF87	4
18	9086	79.88	1.86			202	821	7.22	1.22		
21	8084	71.07	2.1			226	736	6.47	1.30		
23	7278	63.98	2.3			272	610	5.36	1.40		
25	6655	58.51	2.5								
29	5791	50.91	2.9			317	547	4.68	3.07	RX 157	4
						364	476	4.04	3.53	RXF157	4
						412	420	3.57	4.0		
12	13564	119.24	0.90			348	478	4.20	1.63		
13	12516	110.03	0.98			383	452	3.81	1.73		
15	10761	94.60	1.14			432	401	3.38	1.95		
17	9495	83.47	1.29			476	364	3.07	2.1		
20	8200	72.09	1.49	R 147	4	553	313	2.64	2.5	RX 107	4
22	7581	66.65	1.61	RF147	4	635	273	2.30	2.9	RXF107	4
24	6944	61.50	1.76			749	231	1.95	3.1		
28	6014	52.87	2.0			854	203	1.71	3.3		
31	5306	46.65	2.3			1014	171	1.44	3.6		
36	4583	40.29	2.7								
18	9203	80.91	0.82			401	432	3.64	1.30		
20	8359	73.49	0.90			442	391	3.30	1.43		
22	7416	65.20	1.01			500	346	2.92	1.62		
25	6731	59.17	1.12			553	313	2.64	1.79	RX 97	4
29	5785	50.86	1.30			652	266	2.24	2.1	RXF97	4
33	5049	44.39	1.49	R 137	4	745	232	1.96	2.3		
39	4283	37.65	1.76	RF137	4	890	194	1.64	2.4		
44	3744	32.91	2.0			1028	168	1.42	2.5		
49	3362	29.56	2.2								
52	3166	27.83	2.3			529	327	2.76	1.16		
61	2730	24.00	2.7			589	294	2.48	1.29		
66	2520	22.15	3.0			679	255	2.15	1.42	RX 87	4
77	2166	19.04	3.5			756	229	1.93	1.46	RXF87	4
87	1911	16.80	3.9			913	190	1.60	1.56		
37	4536	39.88	0.89			1050	165	1.39	1.65		
42	3963	34.84	1.02								
50	3315	29.14	1.22			22kW					
59	2798	24.60	1.44			11	17645	130.44	0.95		
65	2541	22.34	1.59			12	16366	120.99	1.04		
74	2255	19.82	1.79	R 107	4	14	14124	104.41	1.20		
81	2046	17.99	1.98	RF107	4	16	12464	92.14	1.36		
94	1759	15.46	2.3			18	10805	79.88	1.57		
108	1536	13.50	2.3			21	9614	71.07	1.76	R 167	4
128	1302	11.45	3.1			23	8655	63.98	2.0	RF167	4
146	1139	10.01	3.5			25	7915	58.51	2.1		
181	918	8.07	3.0			29	6887	50.91	2.5		
213	778	6.84	3.6			32	6078	44.93	2.8		
72	2291	20.14	1.07			37	5269	38.95	3.2		
80	2075	18.24	1.13								
90	1839	16.17	1.23			13	14884	110.03	0.83		
100	1663	14.62	1.30			15	12797	94.60	0.95		
118	1409	12.39	1.46			17	11291	83.47	1.08		
135	1232	10.83	1.59	R 97	4	20	9752	72.09	1.3		
158	1053	9.26	1.81	RF97	4	22	9016	66.65	1.36	R 147	4
174	952	8.37	2.0			24	8258	61.50	1.48	RF147	4
206	806	7.09	2.3			28	7152	52.87	1.71		
235	705	6.20	2.5			31	6310	46.65	1.94		
282	589	5.18	2.8			36	5450	40.29	2.2		
328	511	4.49	3.0			41	4821	35.64	2.5		
						49	4051	29.95	3.0		



造型参数表
Selection Table

R

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole
22kW											
22	8820	65.20	0.85			652	316	2.24	1.77		
25	8004	59.17	0.94			745	276	1.96	1.94	RX 97	4
29	6880	50.86	1.09			890	231	1.64	2.05	RXF97	4
33	6005	44.39	1.25			1028	200	1.42	2.14		
39	5093	37.65	1.48								
44	4452	32.91	1.69	R 137 RF137	4	529	389	2.76	0.98		
49	3999	29.56	1.88			589	350	2.48	1.09	RX 87	4
52	3765	27.83	2.00			679	303	2.15	1.19	RXF87	4
61	3246	24.00	2.3			756	272	1.93	1.23		
66	2996	22.15	2.5			913	226	1.60	1.31		
77	2576	19.04	2.9			1050	196	1.39	1.39		
87	2273	16.80	3.3								
101	1963	14.51	3.8								
114	1736	12.83	4.3								
22kW											
42	4713	34.84	0.86			16	16996	92.14	1.0		
50	3942	29.14	1.03			18	14735	79.88	1.15		
59	3328	24.60	1.21			21	13109	71.07	1.29		
65	3022	22.34	1.34			23	11802	63.98	1.43		
74	2681	19.82	1.51			25	10793	58.51	1.57	R 167 RF167	4
81	2434	17.99	1.66			29	9391	50.91	1.80		
94	2091	15.46	1.93	R 107 RF107	4	32	8288	44.93	2.04		
108	1826	13.50	2.2			37	7185	38.95	2.4		
128	1549	11.45	2.6			42	6393	34.66	2.6		
146	1354	10.01	2.7			49	5510	29.87	3.1		
173	1144	8.46	2.9			60	4477	24.27	3.8		
181	1092	8.07	3.0			71	3796	20.58	4.5		
213	925	6.84	3.2								
244	809	5.98	3.5								
30kW											
72	2724	20.14	1.04			17	15397	83.47	0.8		
80	2467	18.24	1.14			20	13298	72.09	0.92		
90	2187	16.17	1.23			22	12294	66.65	0.99		
100	1978	14.62	1.29			24	11261	61.50	1.09		
118	1676	12.39	1.34			28	9752	52.87	1.25		
135	1465	10.83	1.43	R 97 RF97	4	31	8605	46.65	1.42	R 147 RF147	4
158	1253	9.26	1.52			36	7432	40.29	1.64		
174	1132	8.37	1.69			41	6574	35.64	1.86		
206	959	7.09	1.96			49	5525	29.95	2.2		
235	839	6.20	2.1			60	4462	24.19	2.5		
282	701	5.18	2.4			71	3770	20.44	3.0		
325	607	4.49	2.5			81	3328	18.04	3.0		
						93	2885	15.64	4.2		
30kW											
147	1339	9.90	0.83			29	9382	50.86	0.80		
158	1251	9.25	0.91			33	8188	44.39	0.92		
175	1125	8.32	0.97	R 87 RF87	4	39	6945	37.65	1.08		
202	977	7.22	1.03			44	6071	32.91	1.24		
226	875	6.47	1.10			52	5133	27.83	1.41		
272	725	5.36	1.18			61	4427	24.00	1.69		
412	500	3.57	3.36	RX 157 RXF157	4	66	4086	22.15	1.85	R 137 RF137	4
						77	3512	19.04	2.1		
348	592	4.20	1.32			87	3099	16.80	2.4		
383	537	3.81	1.45			101	2676	14.51	2.8		
432	477	3.38	1.64			114	2367	12.83	3.2		
476	433	3.07	1.80			135	1990	10.79	3.8		
553	372	2.64	2.10	RX 107 RXF107	4	192	1400	7.59	3.4		
635	324	2.30	2.41			229	1177	6.38	4.1		
749	275	1.95	2.61								
854	241	1.71	2.75			74	3656	19.82	1.11		
1014	203	1.44	2.99			81	3318	17.99	1.22		
401	513	3.64	1.09			94	2852	15.46	1.42		
442	465	3.30	1.20	RX 97 RXF97	4	108	2490	13.50	1.62		
500	412	2.92	1.36			128	2112	11.45	1.88	R 107 RF107	4
553	372	2.64	1.50			146	1846	10.01	1.91		
						173	1561	8.46	2.2		
						181	1489	8.07	2.2		
						213	1262	6.84	2.5		
						244	1103	5.98	2.6		
						289	933	5.06	2.9		

造型参数表
 Selection Table


输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数	输出转速	输出扭矩	传动比	使用系数	机 型 号	极 数
Output speed	Output torque	Ratio	Service factor	Type	Pole	Output speed	Output torque	Ratio	Service factor	Type	Pole
r/min	Nm	i	f _B	Type	p	r/min	Nm	i	f _B	Type	p
30kW						37kW					
100	2697	14.62	0.80			39	8507	37.65	0.88		
118	2285	12.39	0.90			45	7436	32.91	1.01		
135	1998	10.83	0.98			53	6288	27.83	1.20		
158	1708	9.26	1.12	R 97	4	61	5423	24.00	1.38		
174	1544	8.37	1.24	RF97	4	67	5005	22.15	1.51		
206	1308	7.09	1.44			77	4302	19.04	1.75	R 137	4
235	1144	6.20	1.55			88	3796	16.80	1.98	RF137	4
282	955	5.18	1.75			101	3279	14.51	2.3		
325	828	4.49	1.85			115	2899	12.83	2.6		
						136	2438	10.79	2.8		
432	649	3.40	1.71	RX 127	4	169	1968	8.71	3.1		
				RXF127	4	194	1715	7.59	3.3		
432	623	3.38	1.25			230	1442	6.38	3.7		
476	566	3.07	1.38			285	1164	5.15	3.7		
553	487	2.64	1.60	RX 107	4						
635	424	2.30	1.84	RF107	4	74	4478	19.82	0.90		
749	360	1.95	2.0			82	4065	17.99	0.99		
854	315	1.71	2.1			95	3493	15.46	1.16		
1014	266	1.44	2.3			109	3050	13.50	1.33		
						128	2587	11.45	1.50		
500	539	2.92	1.04			147	2262	10.01	1.56	R 107	4
553	487	2.64	1.15			174	1912	8.46	1.79	RF107	4
652	413	2.24	1.35	RX 97	4	182	1823	8.07	1.8		
745	362	1.96	1.48	RF97	4	215	1546	6.84	2.1		
890	303	1.64	1.57			246	1351	5.98	2.1		
1028	262	1.42	1.63			291	1143	5.06	2.4		
37kW						432	801	3.40	1.39	RX 127	4
18	18049	79.88	0.94			490	707	3.00	1.57	RF127	4
21	16058	71.07	1.05			568	610	2.59	1.82		
23	14456	63.98	1.17								
25	13220	58.51	1.28			435	796	3.38	0.98		
29	11503	50.91	1.47			479	723	3.07	1.08		
33	10152	44.93	1.67	R 167	4	557	622	2.64	1.25	RX 107	4
38	8801	38.95	1.92	RF167	4	639	542	2.30	1.44	RF107	4
42	7831	34.66	2.16			754	459	1.95	1.57		
49	6749	29.87	2.5			860	403	1.71	1.65		
61	5484	24.27	3.1			1021	339	1.44	1.79		
78	4232	18.73	4.0								
90	3685	16.31	4.6								
101	3290	14.56	5.1								
22	15060	66.65	0.81			23	17463	63.98	0.97		
24	13794	61.50	0.89			25	15970	58.51	1.06		
28	11946	52.87	1.02			29	13896	50.91	1.22		
32	10541	46.65	1.16			33	12264	44.93	1.38		
36	9104	40.29	1.34	R 147	4	38	10631	38.95	1.59		
41	8053	35.64	1.52	RF147	4	43	9460	34.66	1.79	R 167	4
49	6767	29.95	1.81			50	8153	29.87	2.08	RF167	4
61	5466	24.19	2.0			61	6624	24.27	2.4		
72	4618	20.44	2.4			72	5617	20.58	2.6		
81	4076	18.04	2.4			79	5112	18.73	3.0		
94	3534	15.64	3.5			91	4452	16.31	3.4		
106	3143	13.91	3.8			102	3974	14.56	3.5		
						28	14431	52.87	0.85		
						32	12733	46.65	0.96		
						37	10997	40.29	1.11		
						42	9728	35.64	1.26		
						49	8175	29.95	1.49		
						61	6603	24.19	1.69		
						72	5579	20.44	2.0	R 147	4
						82	4924	18.04	2.0	RF147	4
						95	4269	15.64	2.9		
						106	3797	13.91	3.2		
						123	3273	11.99	3.7		
						204	1979	7.25	4.1		

R



造型参数表
Selection Table

R

输出转速 Output speed r/min						输出扭矩 Output torque Nm						传动比 Ratio i						使用系数 Service factor f_B						机型号 Type						极数 Pole															
45kW						55kW						75kW						90kW						45kW						55kW															
R						R 137						R 107						RX 127						R 167						R 147															
45	8983	32.91	0.84			78	6352	19.04	1.18			38	17719	38.95	0.95			49	13625	29.95	0.90			43	15767	34.66	1.07			4															
53	7596	27.83	0.99			88	5605	16.80	1.34			43	15767	34.66	1.07			61	11041	24.27	1.43	R	137	4	102	4841	14.51	1.55																	
62	6551	24.00	1.15			102	4841	14.51	1.55			50	13588	29.87	1.25			72	9362	20.58	1.53	RF	137	4	115	4280	12.83	1.76																	
67	6046	22.15	1.24			115	4280	12.83	1.76			61	11041	24.27	1.43			79	8521	18.73	1.81				137	3600	10.79	1.90																	
78	5197	19.04	1.45			120	2906	8.71	2.1			79	8521	18.73	1.81			91	7420	16.31	2.03				195	2532	7.59	2.3																	
88	4586	16.80	1.64	R	137	4	232	2128	6.38	2.5			102	6624	14.56	2.13			119	5646	12.41	3.0				287	1718	5.15	2.5																
102	3960	14.51	1.90	RF	137	4	387	1242	3.57	1.35			144	4677	10.28	3.4			415	1242	3.57	1.35	RX	157	4	479	1075	3.09	1.56	RXF	157	4													
115	3502	12.83	2.1			493	968	3.40	1.15			169	3990	8.77	4.0			493	854	3.00	1.30				571	737	2.59	1.51	RX	127	4	646	652	2.29	1.70	RXF	127	4							
137	2945	10.79	2.3			767	549	1.93	2.02			438	962	3.38	0.81			767	915	1.93	1.21				482	874	3.07	0.89				561	751	2.64	1.04	RX	107	4	643	654	2.30	1.19	RXF	107	4
170	2377	8.71	2.6			767	549	1.93	2.02			759	555	1.95	1.30			759	555	1.95	1.30				759	555	1.95	1.30				865	487	1.71	1.36				1028	410	1.44	1.48			
195	2072	7.59	2.8			296	2275	5.00	3.6			479	1466	3.09	1.15			767	915	1.93	1.21				493	854	3.00	1.30				571	737	2.59	1.51	RX	127	4	646	652	2.29	1.70	RXF	127	4
232	1741	6.38	3.1			493	968	3.40	1.15			767	915	1.93	1.21			493	854	3.00	1.30				767	915	1.93	1.21				767	915	1.93	1.21				767	915	1.93	1.21			
287	1406	5.15	3.1			493	968	3.40	1.15			949	740	1.56	1.50			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30			
561	12984	38.95	1.00			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
571	14989	44.93	1.13			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
591	11563	34.66	1.46			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
61	9963	29.87	1.70	R	167	4	493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30									
72	8097	24.27	1.96	RF	167	4	493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30									
79	6866	20.58	2.09			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
79	6248	18.73	2.50			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
91	5441	16.31	2.76			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
102	4857	14.56	2.90			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
119	4140	12.41	4.09			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
144	3429	10.28	4.66			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
32	15563	46.65	0.8			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
37	13441	40.29	0.91			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
42	11890	35.64	1.03			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
49	9991	29.95	1.22			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
61	8070	24.19	1.39			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
72	6819	20.44	1.65			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
82	6018	18.04	1.64	R	147	4	493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30									
95	5218	15.64	2.3	RF	147	4	493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30									
106	4640	13.91	2.6			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
123	4000	11.99	3.1			493	854	3.00	1.30			493	854	3.00	1.30			493	854	3.00	1.30				493	854	3.00	1.30				493	854	3.00	1.30										
152	3249	9.74	3.8			493	854	3.00	1.30			493																																	



输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f_B	机型号 Type	极数 Pole p
90kW											
72	11158	20.44	1.01								
82	9848	18.04	1.10								
95	8538	15.64	1.43								
106	7593	13.91	1.56	R 147	4						
123	6545	11.99	1.87	RF147	4						
156	5170	9.47	2.1								
179	4509	8.26	2.4								
204	3958	7.25	2.5								
251	3215	5.89	2.7								
296	2729	5.00	3.0								
542	1555	2.75	1.08	RX 157	4						
629	1340	2.37	1.25	RXF157	4						
772	1091	1.93	1.54								
955	882	1.56	1.26	RX 127	4						
				RXF127	4						
110kW											
61	16193	24.27	1.04								
72	13731	20.58	1.23								
91	10882	16.31	1.38	R 167	4						
102	9715	14.56	1.45	RF167	4						
119	8280	12.41	2.04								
144	6859	10.28	2.3								
169	5851	8.77	2.7								
629	1638	2.37	1.03	RX 157	4						
772	1334	1.93	1.26	RXF157	4						
914	1126	1.63	1.49								
132kW											
72	16477	20.58	1.03								
91	13059	16.31	1.15								
102	11657	14.56	1.21	R 167	4						
119	9936	12.41	1.70	RF167	4						
144	8231	10.28	1.94								
169	7022	8.77	2.28								
914	1351	1.63	1.24	RX 157	4						
				RXF157	4						
160kW											
120	11963	12.41	1.41	R 167	4						
145	9910	10.28	1.61	RF167	4						
170	8484	8.77	1.89								

R



造型参数表
Selection Table

R

	Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio	机型号 Type	功率 Power kW/4p		Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio	机型号 Type	功率 Power kW/4p
130	8.5	164				0.18	0.82	1690			0.18
	8.9	156					0.91	1524			
	10	135	R 27R17				1.0	1395			
	12	118	RF27R17				1.1	1232			
	13	104					1.2	1145			0.25
	15	90					1.3	1037			
200	4.8	289				0.18	1.6	883			
	5.7	243					1.7	802			0.37
	6.2	226					1.8	754			
	7.5	185					1.4	1008			
	8.5	164	R 37R17				2.0	683			
	8.9	156	RF37R17				2.3	599	R 87R57	0.55	
300	10	135				0.25	2.6	538	RF87R57		
	11	127					2.9	472			
	13	104					3.4	400			
	15	90					3.5	396			0.75
	3.2	429					3.9	361			
	3.7	372					4.0	351			
450	4.0	348	R 47R37			0.18	4.6	305			
	4.6	301	RF47R37				4.7	300			
	5.5	255					5.2	267			1.1
	6.1	228					5.5	256			
	2.1	678					0.32	4309			
	2.4	589					0.35	4004			
600	2.6	537				0.18	0.38	3702			0.18
	3.0	471	R 57R37				0.40	3481			
	3.9	357	RF57R37				0.46	3019			
	4.4	319					0.52	2668			
	5.2	267					0.62	2245			0.25
	5.8	241					0.69	2016			
820	1.7	836				0.18	0.76	1823			
	1.9	750					0.80	1733			
	2.0	730					0.86	1623			0.37
	2.2	630					0.88	1583			
	2.4	571					0.97	1434			
	2.5	561	R 67R37				1.00	1396			
1550	2.8	495				0.25	1.1	1228			
	2.9	486					1.2	1207			
	3.2	438					1.3	1084	R 97R57	0.55	
	3.6	388					1.3	1068	RF97R57		
	4.1	336					1.5	937			
	4.8	287					1.6	934			
1550	1.2	1124				0.18	1.7	824			
	1.3	1047					1.8	755			0.75
	1.5	915					1.9	737			
	1.6	858					2.1	631			
	1.8	757					2.2	625			
	2.1	671					2.5	549			1.1
1550	2.4	571				0.25	2.6	560			
	2.5	547	R 77R37				2.9	484			
	2.9	477	RF77R37				3.2	430			
	3.3	426					3.7	379			1.5
	3.8	364					4.1	336			
	4.5	312					4.7	296			
1550	4.5	310				0.55	5.1	270			
	5.6	248					5.6	249			2.2
	0.65	2129					5.9	234			
	0.71	1955	R 87R57				6.1	227			
	0.72	1930	RF87R57								
	0.79	1737									
	0.80	1733									


表上所配功率均有超载,按实际条件确定的转扭不得大于减速机额定转扭。 The power are all overload in the table. The decided torque according to operating condition should not more than gear units' nominal torque.

造型参数表
 Selection Table


Mamax Permissible torque	输出转速 Output speed	传动比 Ratio	机型号 Type	功率 Power	Mamax Permissible torque	输出转速 Output speed	传动比 Ratio	机型号 Type	功率 Power
Nm	r/min	i	Type	kW/4p	Nm	r/min	i	Type	kW/4p
4300	0.21 0.24 0.27 0.32 0.36 0.36 0.42 0.46 0.46 0.53 0.62 0.68 0.71 0.77 0.83 0.88 0.91 1.00 1.00 1.14 1.2 1.27 1.3 1.50 1.6 1.7 2.0 2.3 2.4 2.6 2.7 2.9 3.1 3.4 3.5 3.8 4.0 4.5 4.6 5.1 5.2 5.7 5.8 6.6 6.9 7.5 7.9 8.6	6690 5735 5127 4302 3870 3847 3302 3015 2997 2621 2252 2041 1971 1813 1673 1587 1531 1390 1389 1216 1194 1095 1043 927 888 787 692 605 598 530 510 479 463 420 406 373 357 321 313 281 277 253 245 217 208 191 181 167	0.18 0.25 0.37 0.55 0.75 R 107R77 RF107R77 1.1 1.5 2.2 3 4	0.34 0.35 0.40 0.41 0.42 0.47 0.48 0.52 0.56 0.58 0.62 0.67 0.75 0.76 0.88 1.0 1.1 1.3 1.3 1.4 1.5 1.6 1.7 2.0 2.1 2.3 2.3 2.6 2.6 2.8 2.9 3.2 3.4 3.8 3.8 4.2 4.5 4.8 5.0 5.8 0.08 0.09 0.10 0.12 0.13 0.15 0.17 0.20 0.22 0.26 0.30 0.33 0.39 0.44 0.50	4018 3928 3514 3377 3338 2929 2926 2658 2484 2412 2242 2073 1863 1839 1598 1397 1226 1090 1080 1020 951 869 831 730 684 629 609 564 549 517 490 453 428 376 374 339 317 297 286 250 18210 15923 14075 12344 11143 9743 8443 7307 6447 5568 4815 4325 3669 3228 2833	0.37 0.55 0.75 1.1 1.5 2.2 3 4 5.5 0.18 0.25 R 137R77 RF137R77 0.37 0.55 0.75			
8000	0.12 0.13 0.16 0.19 0.22 0.24 0.28 0.30 0.32	11712 10573 8784 7479 6412 5834 5001 4709 4364	0.18 0.25 0.37	R 137R77 RF137R77	0.18 0.25 0.37	0.26 0.30 0.33 0.39 0.44 0.50	5568 4815 4325 3669 3228 2833	R 147R77 RF147R77	0.37

表上所配功率均有超载,按实际条件确定的转扭不得大于减速机额定转扭。 The power are all overload in the table. The decided torque according to operating condition should not more than gear units' nominal torque.

R




造型参数表
Selection Table

R


Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio	机型号 Type	功率 Power kW/4p	Mamax Permissible torque Nm	输出转速 Output speed r/min	传动比 Ratio	机型号 Type	功率 Power kW/4p
13000	0.56 0.65 0.73 0.84 0.93 1.1 1.2 1.4 1.6 1.8 2.1 2.4 2.6 3.0 2.7 3.1 3.3 3.9 4.4 6.8	2555 2211 1951 1705 1536 R 147R77 RF147R77 1029 889 784 695 607 547 480 540 462 432 RF147R87 373 330 216		1.1 1.5 2.2 3 4 5.5 4 5.5 7.5 11	4.9 5.1 5.2 5.6 6.1 6.5 7.0 7.5 295 287 281 260 238 224 208 195			R 167R107 RF167R107	11 15
18000	0.05 0.06 0.07 0.08 0.09 0.10 0.12 0.13 0.14 0.23 0.26 0.30 0.33 0.18 0.20 0.37 0.54 0.61 0.69 0.76 0.86 0.98 1.1 1.3 1.4 1.7 1.9 2.2 2.5 2.8 3.3 3.8 4.3 4.8 5.2	27001 22482 20002 17361 15446 14051 11812 10519 9754 6069 5399 4709 4182 7749 6894 3739 2657 2333 2085 R 167R97 RF167R97 1877 1670 1456 1296 1137 1012 872 770 664 578 510 438 380 338 307 282		0.55 0.75 1.1 1.5 2.2 3 4 5.5 7.5 11					

表上所配功率均有超载,按实际条件确定的转扭不得大于减速机额定转扭。 The power are all overload in the table. The decided torque according to operating condition should not more than gear units' nominal torque.


RX37




RX..S37



RXF37



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y ₂ 电机机座号 Motor size	63	71	80	90S	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75
L3	223	236	264	301	
G	130	145	175	195	
L2	71	71	71	71	

注：“RX..”表示RX、RXF



Note:"RX.."mean RX、RXF

外形安装尺寸
Mounting Dimension Sheets-Overview



RX57




RX..S57





RXF57





电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



Φ160



Φ200



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100	112M	132S	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0
L3	223	245	278	304	328	350	380	425	
G	130	145	175	195	195	215	240	275	
L2	81	81	81	81	81	93	93	101	


注：“RX..” 表示RX、RXF

Note: "RX.." mean RX, RXF


外形及裝尺寸 Mounting Dimensions/Size-overview



RX67




RX..S67




RXF67

Φ160




A technical drawing of a bearing assembly. It features two concentric rings. The outer ring has a bore diameter of $\phi 130$ mm, indicated by a dimension line with arrows pointing to the inner edge. The inner ring has an outer diameter of $\phi 9$ mm, indicated by a dimension line with arrows pointing to the outer edge. A horizontal dimension line at the top spans the distance between the outer edges of the two rings, labeled as 146 mm.

Φ200




A technical drawing of a bearing assembly. It features two concentric rings. The outer ring has a bore diameter of $\phi 165$ and a width of 146. The inner ring has a bore diameter of $\phi 11$. The overall width of the bearing is indicated as 146.

Φ250



A technical drawing of a bearing assembly. It features two concentric rings. The outer ring has a bore diameter of $\phi 13.5$ and an outer diameter of $\phi 215$. The inner ring has an outer diameter of 146 . The width of the bearing is indicated as 10 .

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	63	71		80		90S	90L	100		112M	132S	132M	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	
L3	223	245		278		304	328	350		380	425	461	
G	130	145		175		195	195	215		240	275	275	
L2	81	81		81		81	81	93		93	101	101	

注：“RX..”表示RX、RXF


Note: "RX.." mean RX, RXF

外形安装尺寸
Mounting Dimension Sheets-Overview

RX77





RX..S77






RXF77

Φ200



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

Φ250



注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsite structure

Y ₂ 电机机座号 Motor size	90S	90L	100	112M	132S	132M	160M	
功率/4P Power(kW)	1.1	1.5	2.2 3.0	4.0	5.5	7.5	11	
L3	304	328	350	380	425	461	524	
G	195	195	215	240	275	275	330	
L2	81	81	93	93	101	101	126	


注：“RX..”表示RX、RXF

Note:"RX.."mean RX、RXF


外形及装尺寸
Mounting Dimension Sheets-over view




RX87




RX..S87




RXF87



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



Φ300



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure.



Y ₂ 电机机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	
功率/4P Power/(kW)	3.0	4.0	5.5	7.5	11	15	18.5	22	
L3	351	380	425	461	524	547	583	616	
G	215	240	275	275	330	330	380	380	
L2	71	71	101	101	126	126	126	126	

注：“RX..”表示RX、RXF


Note:"RX.." mean RX, RXF

外形安装尺寸
Mounting Dimension Sheets-Overview


RX97






RX..S97



RXF97



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	132S	132M	160M	160L	180M	180L	200	
功率/4P Power(kW)	5.5	7.5	11	15	18.5	22	30	
L3	425	461	524	547	555	588	654	
G	275	275	330	330	380	380	420	
L2	101	101	126	126	126	126	126	



注：“RX..”表示RX、RXF

Note:"RX.."mean RX、RXF


外形及装尺寸
Mounting Dimension Sheets-over view




RX107




RX..S107





RXF107



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



Φ450



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure.


Y2电机机座号 Motor size	132M	160M	160L	180M	180L	200	225S	225M	
功率/4P Power/(kW)	7.5	11	15	18.5	22	30	37	45	
L3	422	504	519	555	588	654	680	702	
G	275	330	330	380	380	420	470	470	
L2	101	126	126	126	126	132	132	132	

注：“RX..”表示RX、RXF


Note:"RX.."mean RX, RXF

外形安装尺寸
Mounting Dimension Sheets-Overview

RX127






RX..S127



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.


RXF127




注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsite structure

Y ₂ 电机机座号 Motor size	132M	160M	160L	180M	180L	200	225S	225M	250	280S	280M
功率/4P Power(kW)	7.5	11	15	18.5	22	30	37	45	55	75	90
L3	424	567	602	583	616	654	674	696	775	845	845
G	275	330	330	380	380	420	470	470	510	580	580
L2	132	132	132	132	132	132	143	143	120	120	120

RX157






RX..S157



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

RXF157





注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsite structure

Y ₂ 电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M
功率/4P Power(kW)	11	15	18.5	22	30	37	45	55	75	90	110	132
L3	567	602	635	666	642	669	691	770	828	879	1100	1130
G	330	330	380	380	420	470	470	510	580	580	645	645
L2	143	143	143	143	143	143	143	143	143	143	145	145




注：“RX..” 表示RX、RXF

Note: "RX.." mean RX、RXF

外形及装尺寸
Mounting Dimension Sheets-over view



R17

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF17****Φ120**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

R


Φ140

Y2电机机座号 Motor size	63	71	80						
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75				
L3	235	245	278						
G	130	145	175						
L2	71	71	71						






注：“R..”表示R、RF

Note:"R.." mean R、RF

外形安装尺寸
Mounting Dimension Sheets-Overview

R27

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



**R****RF27****R..S27****R..27R17**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure







Y2电机机座号 Motor size	63	71	80	90S	90L	100	
功率/4P Power/(kW)	0.18	0.25 0.37	0.55 0.75	1.1	1.5	2.2 3.0	
L3	235	245	278	304	328	340	
G	130	145	175	195	195	215	
L2	71	71	71	71	71	93	

注：“R..”表示R、RF Note: "R.." mean R、RF

外形及装尺寸
Mounting Dimension Sheets-over view

R37

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF37****R..S37****R..37R17**


注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100L	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5
L3	235	245	278	304	328	340	
G	130	145	175	195	195	215	
L2	71	71	71	71	71	93	






注：“R..”表示R、RF

Note: "R.." mean R, RF

外形安装尺寸
Mounting Dimension Sheets-Overview

R47

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF47****Φ160****R..S47****Φ200****R..47R37**


注：其余尺寸见相应的结构形式
Note: For other values please refer to the oppsite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100	112M	132S	
功率/4P Power(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0
L3	223	245	278	304	328	350	380	425	
G	130	145	175	195	195	215	240	275	
L2	81	81	81	81	81	93	93	101	






注：“R..”表示R、RF

Note:"R.."mean R、RF

外形及装尺寸
Mounting Dimension Sheets-over view

R57

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF57****Φ200****R..S57****Φ250****R..57R37**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	132M	
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0
L3	223	245	278	304	328	350	380	425	461	
G	130	145	175	195	195	215	240	275	275	
L2	81	81	81	81	81	93	93	101	101	



注：“R..”表示R、RF

Note:"R.."mean R、RF




外形安装尺寸
Mounting Dimension Sheets-Overview

R67





电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF67



Φ200




R..S67



Φ250



R..67R37





注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	132M
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0
L3	223	245	278	304	328	350	380	425	461
G	130	145	175	195	195	215	240	275	275
L2	81	81	81	81	81	93	93	101	101








注：“R..”表示R、RF

Note:"R.."mean R、RF

外形及装尺寸
Mounting Dimension Sheets-over view

R77

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF77****Φ250****Φ300****R..S77****R..77R37**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	63	71	80	90S	90L	100L	112M	132S	132M	160M
功率/4P Power/(kW)	0.18	0.25	0.37	0.55	0.75	1.1	1.5	2.2	3.0	4.0
L3	223	233	278	304	328	350	380	425	461	524
G	130	145	175	195	195	215	240	275	275	330
L2	81	81	81	81	81	93	93	101	101	126


注：“R..”表示R、RF

Note:"R.."mean R、RF




外形安装尺寸
Mounting Dimension Sheets-Overview


R87




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF87




R..S87



Φ300



R..87R57



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure


Y2电机机座号 Motor size	80	90S	90L	100	112M	132S	132M	160M	160L	180M	180L
功率/4P Power/(kW)	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	15
L3	246		280	304	350	380	425	461	524	547	583
G	175		195	195	215	240	275	275	330	330	380
L2	86		86	86	71	71	101	101	126	126	126

注：“R..”表示R、RF

Note: "R.." mean R, RF




R97



电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connect.


RF97

Φ 350



R..S97

Φ450



R..97R57

A technical drawing of a pump assembly. It features a motor on the left connected by a shaft to a pump body. The pump body has a vertical dimension of 196 and a horizontal dimension of L3. A flange with two bolts is attached to the right side of the pump body. The letters 'G' are printed at the bottom right.


注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposed structure

Y2电机机座号 Motor size	80	90S	90L	100	112M	132S	132M	160M	160L	180M	180L	200		
功率/4P Power(kW)	0.55	0.75	1.1	1.5	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22	30
L3	246	280	304	315	334	425	461	524	547	555	588	654		
G	175	195	195	215	240	275	275	330	330	380	380	420		
L2	86	86	86	101	101	101	101	126	126	126	126	132		






注：“R₁”表示R、RF

Note: "R," mean R, RF

外形安装尺寸
Mounting Dimension Sheets-Overview

R107

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.



**RF107****Φ350****R..S107****Φ450****R..107R77**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure






Y2电机机座号 Motor size	100	112M	132S	132M	160M	160L	180M	180L	200	225S	225M	
功率/4P Power(kW)	2.2	3.0	4.0	5.5	7.5	11	15	18.5	22	30	37	45
L3	318	334	386	422	504	519	555	588	654	680	702	
G	215	240	275	275	330	330	380	380	420	470	470	
L2	101	101	101	101	126	126	126	126	132	132	132	

注：“R..”表示R、RF Note: "R.." mean R、RF

外形及装尺寸
Mounting Dimension Sheets-over view

R137

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF137****Φ450****R..S137****Φ550****R..137R77**

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	132S	132M	160M	160L	180M	180L	200	225S	225M	250	
功率/4P Power/(kW)	5.5	7.5	11	15	18.5	22	30	37	45	55	
L3	388	424	476	519	555	588	654	680	702	771	
G	275	275	330	330	380	380	420	470	470	510	
L2	126	126	132	132	132	132	132	143	143	174	


注：“R..”表示R、RF

Note:"R.." mean R、RF




外形安裝尺寸 Mounting Dimension Sheets-Overview

R147




电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.




RF147


Φ 450




R..S147



Φ550



R..147R87(R77)



	R..147R77组合	R..147R87组合
L	226	275



注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	
L3	567	602	583	616	654	674	696	775	845	845	
G	330	330	380	380	420	470	470	510	580	580	
L2	132	132	132	132	132	143	143	174	174	174	








注：“R..”表示R、RF

Note: "R.." mean R, RF

外形及装尺寸
Mounting Dimension Sheets-over view

R167

电机需方配时或配特殊电机时需加联接法兰
When equipping the user's motor or the special one, the flange is required to connected.

**RF167****Φ550****Φ660****R..S167****R..167R97(R107)**

	R..167R97组合	R..167R107组合
L	320	370

注：其余尺寸见相应的结构形式
Note: For other values please refer to the opposite structure

Y2电机机座号 Motor size	160M	160L	180M	180L	200	225S	225M	250	280S	280M	315S	315M	315L
功率/4P Power/(kW)	11	15	18.5	22	30	37	45	55	75	90	110	132	160
L3	567	602	635	666	642	669	691	770	828	879	1100	1130	1360
G	330	330	380	380	420	470	470	510	580	580	645	645	645
L2	143	143	143	143	143	143	143	113	113	113	113	145	145

注：“R..”表示R、RF

Note: "R.." mean R, RF

R